DATASHEET



2 gang 13A Double Pole Switched Socket with 2 USB

Code: 71SS2USBULTPB-B

Hartland | HARTLAND RANGE | USB Power Sockets

Insert Type

Maximum Load

Product Image




Wiring



Dimensions





31	Outlets 2x2.4A (4.8A Total)
Insert Colour	Polished Brass/Black
EAN13 Barcode	5017504089948
Commodity Code	85363010
Luckins TSI	405688234
ETIM Class	EC000125
Dimensions (Nominal)	Double: Height = 88.0mm Width = 144.5mm Depth = 5.0mm
Weight	241 GR
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = N/A
Minimum Wall Box Depth	35mm
Switched Poles	Double
Current Rating	13 Amp, USB 2 x 2.4A
Voltage	180/250V AC USB = 5V

13 Amp, USB = 2.4A X 2

Mains Frequency 50/60Hz

IP Rating IP2XD

Contact Gap Minimum 3mm

Terminal Capacity 1 3x2.5mm²

Terminal Capacity 2 3x4mm²

Terminal Capacity 3 2x6mm² Multi-Strand

Earth Terminal Capacity 1 3x2.5mm²
Earth Terminal Capacity 2 3x4mm²

Earth Terminal Capacity 3 2x6mm² Multi-Strand

zaren reminar capacity 5

Ambient Operating -15°C to +40°C Temperature

Recommended Location Internal Use Only

Maximum Installation 2000m

Altitude

Product Class 1

Standard/Approval BS1363 BS EN 62368

Patents And Trade Marks Hartland is a Registered Trade Mark No. 2344778

Must be earthed

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.cor

(WFR

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 29/04/2024 FSOE