## **DATASHEET**




Code: 74R22SS-B

# Hartland | HARTLAND RANGE | Rocker Switches

#### **Product Image**



#### Wiring



### Dimensions

Insert Type	2 gang 10AX 2 Way Rocker
Insert Colour	Satin Steel/Black
EAN13 Barcode	5017503246229
Commodity Code	85363010
Luckins TSI	385553049
ETIM Class	EC001590
Dimensions(Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm
Weight	111 GR
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A
Minimum Wall Box Depth	25mm
Switched Poles	Single
Current Rating	10AX
Voltage	220/250V AC
Maximum Load	10 Amp inductive
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Terminal Capacity 1	5x1mm²
Terminal Capacity 2	4x1.5mm²
Terminal Capacity 3	1x2.5mm²
Terminal Capacity 4	1x4mm² Multi-strand
<b>Terminal Capacity 5</b>	1x6mm²
Earth Terminal Capacity 1	5x1mm²
Earth Terminal Capacity 2	4x1.5mm²
Earth Terminal Capacity 3	3x2.5mm²
Earth Terminal Capacity 4	1x4mm² Multi-strand
Earth Terminal Capacity 5	1x6mm²
Product Class 1	Must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,

**T:** +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.com


All accessories are manufactured under an accredited by ENISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 19/05/2024 F&OF

## **DATASHEET**



Code: 74R22SS-B

## Hartland | HARTLAND RANGE | Rocker Switches



Maximum Installation Altitude	2000m
Standard/Approval	BS EN 60669-1
Patents And Trade Marks	Hartland is a Registered Trade Mark No. 2344778