## **DATASHEET**




Code: 74SPNWH-W

# Hartland | HARTLAND RANGE | Connection Units

### **Product Image**



### Wiring



#### **Dimensions**



Insert Colour White/White EAN13 Barcode 5017503240920 Commodity Code 85369010 Luckins TSI 385553450 ETIM Class EC001590 Dimensions(Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 2x4mm² Multi-Strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 4 2x4mm² Multi-Strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 2x4mm² Multi-Strand Earth Terminal Capacity 7 1x6mm² Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 9 1x6mm² Earth Terminal Capacity 9 1x6mm² Earth Terminal Capacity 1 1x6mm² Earth Terminal Capacity 1 1x6mm² Earth Terminal Capacity 1 1x6mm² Earth Terminal Capacity 3 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-Strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 9 1x6mm² Earth Terminal Capacity 9 1x6mm² Earth Terminal Capacity 1 1x6mm² Earth Terminal Capacity 9 1x6mm²	Insert Type	1 gang 13A Double Pole Fused Spur + Neon
Commodity Code Luckins TSI 385553450  ETIM Class EC001590  Dimensions(Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 35mm  Switched Poles Double Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 2x4mm² Multi-Strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 1 5x1.5mm² Earth Terminal Capacity 4 2x4mm² Multi-Strand Earth Terminal Capacity 4 2x4mm² Multi-Strand Earth Terminal Capacity 5 1x6mm² Farth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS 1363-4	Insert Colour	White/White
Luckins TSI 385553450  ETIM Class EC001590  Dimensions(Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm  Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A  Minimum Wall Box Depth 35mm  Switched Poles Double  Current Rating 13 Amp  Voltage 220/250V AC  Maximum Load 13 Amp  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²  Earth Terminal Capacity 1 5x1.5mm²  Earth Terminal Capacity 2 5x1.5mm²  Earth Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 4 2x4mm² Multi-Strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating Temperature  Recommended Location Internal Use Only  Maximum Installation Altitude  Standard/Approval BS 1363-4	EAN13 Barcode	5017503240920
ETIM Class  Dimensions(Nominal)  Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm  Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = N/A  Minimum Wall Box Depth  Switched Poles  Current Rating  13 Amp  Voltage  220/250V AC  Maximum Load  13 Amp  Mains Frequency  50Hz  IP Rating  IP2XD  Contact Gap Minimum  3mm  Terminal Capacity 1  Terminal Capacity 2  2x4mm² Multi-Strand  Terminal Capacity 3  Earth Terminal Capacity 1  5x1.5mm²  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Ix6mm²  Earth Terminal Capacity 5  Terminal Capacity 6  Xx2.5mm²  Earth Terminal Capacity 6  Xx2.5mm²  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal Capacity 9  Earth Terminal Capacity 5  Ix6mm²  Must be earthed  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation  Altitude  Standard/Approval  BS 1363-4	Commodity Code	85369010
Dimensions(Nominal)  Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm  Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = N/A  Minimum Wall Box Depth  Switched Poles  Double  Current Rating  13 Amp  Voltage  220/250V AC  Maximum Load  13 Amp  Mains Frequency  IP Rating  IP2XD  Contact Gap Minimum  Terminal Capacity 1  Terminal Capacity 2  2x4mm² Multi-Strand  Terminal Capacity 3  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Ix6mm²  Earth Terminal Capacity 5  Ix6mm²  Must be earthed  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation  Altitude  Standard/Approval  BS 1363-4	Luckins TSI	385553450
Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = N/A  Minimum Wall Box Depth  Switched Poles  Double  Current Rating  13 Amp  Voltage  220/250V AC  Maximum Load  13 Amp  Mains Frequency  IP Rating  IP2XD  Contact Gap Minimum  Terminal Capacity 1  3x2.5mm²  Terminal Capacity 2  2x4mm² Multi-Strand  Terminal Capacity 3  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Ix6mm²  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal Capacity 1  Earth Terminal Capacity 5  Ix6mm²  Product Class 1  Must be earthed  Ambient Operating  Temperature  Recommended Location  Internal Use Only  Maximum Installation  Altitude  Standard/Approval  BS 1363-4	ETIM Class	EC001590
Minimum Wall Box Depth 35mm  Switched Poles Double  Current Rating 13 Amp  Voltage 220/250V AC  Maximum Load 13 Amp  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²  Earth Terminal Capacity 2 5x1.5mm²  Earth Terminal Capacity 3 3x2.5mm²  Earth Terminal Capacity 4 2x4mm² Multi-Strand  Earth Terminal Capacity 5 1x6mm²  Earth Terminal Capacity 5 1x6mm²  Earth Terminal Capacity 6 2x4mm² Multi-Strand  Earth Terminal Capacity 7 1x6mm²  Product Class 1 Must be earthed  Ambient Operating -5° to +40°C  Temperature  Recommended Location Internal Use Only  Maximum Installation Altitude  Standard/Approval BS 1363-4	Dimensions(Nominal)	· ·
Switched PolesDoubleCurrent Rating13 AmpVoltage220/250V ACMaximum Load13 AmpMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 13x2.5mm²Terminal Capacity 22x4mm² Multi-StrandTerminal Capacity 31x6mm²Earth Terminal Capacity 16x1mm²Earth Terminal Capacity 33x2.5mm²Earth Terminal Capacity 42x4mm² Multi-StrandEarth Terminal Capacity 51x6mm²Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalBS 1363-4	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A
Current Rating 13 Amp  Voltage 220/250V AC  Maximum Load 13 Amp  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²  Earth Terminal Capacity 2 5x1.5mm²  Earth Terminal Capacity 3 3x2.5mm²  Earth Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 4 2x4mm² Multi-Strand  Earth Terminal Capacity 4 2x4mm² Multi-Strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating Temperature  Recommended Location Internal Use Only  Maximum Installation Altitude  Standard/Approval BS 1363-4	Minimum Wall Box Depth	35mm
Voltage 220/250V AC  Maximum Load 13 Amp  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²  Earth Terminal Capacity 2 5x1.5mm²  Earth Terminal Capacity 3 3x2.5mm²  Earth Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 4 2x4mm² Multi-Strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating 1-5° to +40°C  Temperature  Recommended Location Internal Use Only  Maximum Installation 2000m  Altitude  Standard/Approval BS 1363-4	Switched Poles	Double
Maximum Load  13 Amp  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 2x4mm² Multi-Strand  Earth Terminal Capacity 4 2x4mm² Multi-Strand  Earth Terminal Capacity 5 Product Class 1 Must be earthed  Ambient Operating Temperature  Recommended Location Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS 1363-4	Current Rating	13 Amp
Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²  Earth Terminal Capacity 2 5x1.5mm²  Earth Terminal Capacity 3 3x2.5mm²  Earth Terminal Capacity 4 2x4mm² Multi-Strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating Temperature  Recommended Location Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS 1363-4	Voltage	220/250V AC
IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²  Earth Terminal Capacity 2 5x1.5mm²  Earth Terminal Capacity 3 3x2.5mm²  Earth Terminal Capacity 4 2x4mm² Multi-Strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating Temperature  Recommended Location Internal Use Only  Maximum Installation Altitude  Standard/Approval BS 1363-4	Maximum Load	13 Amp
Contact Gap Minimum  Terminal Capacity 1  Terminal Capacity 2  2x4mm² Multi-Strand  Terminal Capacity 3  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Maximum Installation Altitude  Standard/Approval  3x2.5mm²  2x4mm² Multi-Strand  Earth Terminal Capacity 5  1x6mm²  Product Class 1  Must be earthed  -5° to +40°C  Temperature  Recommended Location  Internal Use Only  Maximum Installation  Altitude  Standard/Approval	Mains Frequency	50Hz
Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²  Earth Terminal Capacity 2 5x1.5mm²  Earth Terminal Capacity 3 3x2.5mm²  Earth Terminal Capacity 4 2x4mm² Multi-Strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating 75° to +40°C  Temperature  Recommended Location Internal Use Only  Maximum Installation Altitude  Standard/Approval BS 1363-4	IP Rating	IP2XD
Terminal Capacity 2  2x4mm² Multi-Strand  1x6mm²  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  2x4mm² Multi-Strand  Earth Terminal Capacity 4  2x4mm² Multi-Strand  Earth Terminal Capacity 5  Product Class 1  Must be earthed  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS 1363-4	Contact Gap Minimum	3mm
Terminal Capacity 3	Terminal Capacity 1	3x2.5mm²
Earth Terminal Capacity 1 6x1mm²  Earth Terminal Capacity 2 5x1.5mm²  Earth Terminal Capacity 3 3x2.5mm²  Earth Terminal Capacity 4 2x4mm² Multi-Strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating 7-5° to +40°C  Temperature  Recommended Location Internal Use Only  Maximum Installation Altitude  Standard/Approval BS 1363-4	Terminal Capacity 2	2x4mm² Multi-Strand
Earth Terminal Capacity 2 5x1.5mm²  Earth Terminal Capacity 3 3x2.5mm²  Earth Terminal Capacity 4 2x4mm² Multi-Strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating -5° to +40°C  Temperature  Recommended Location Internal Use Only  Maximum Installation Altitude  Standard/Approval BS 1363-4	Terminal Capacity 3	1x6mm²
Earth Terminal Capacity 3 3x2.5mm²  Earth Terminal Capacity 4 2x4mm² Multi-Strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating -5° to +40°C  Temperature  Recommended Location Internal Use Only  Maximum Installation Altitude  Standard/Approval BS 1363-4	Earth Terminal Capacity 1	6x1mm²
Earth Terminal Capacity 4 2x4mm² Multi-Strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating -5° to +40°C  Temperature  Recommended Location Internal Use Only  Maximum Installation Altitude  Standard/Approval BS 1363-4	Earth Terminal Capacity 2	5x1.5mm²
Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating -5° to +40°C  Temperature  Recommended Location Internal Use Only  Maximum Installation 2000m  Altitude  Standard/Approval BS 1363-4	Earth Terminal Capacity 3	3x2.5mm²
Product Class 1 Must be earthed  Ambient Operating -5° to +40°C  Temperature  Recommended Location Internal Use Only  Maximum Installation 2000m  Altitude  Standard/Approval BS 1363-4	Earth Terminal Capacity 4	2x4mm² Multi-Strand
Ambient Operating Temperature  Recommended Location Internal Use Only  Maximum Installation Altitude  Standard/Approval BS 1363-4	Earth Terminal Capacity 5	1x6mm²
Temperature  Recommended Location Internal Use Only  Maximum Installation 2000m  Altitude  Standard/Approval BS 1363-4	Product Class 1	Must be earthed
Maximum Installation 2000m Altitude  Standard/Approval BS 1363-4		-5° to +40°C
Altitude Standard/Approval BS 1363-4	Recommended Location	Internal Use Only
		2000m
Patents And Trade Marks Hartland is a Registered Trade Mark No. 2344778	Standard/Approval	BS 1363-4
	Patents And Trade Marks	Hartland is a Registered Trade Mark No. 2344778

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

**T:** +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.com

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 19/05/2024 E&OE