DATASHEET



Code: 7745SS1BC-B


Hartland | HARTLAND RANGE | Double Pole Switches

Product Image



Wiring

Dimensions



Insert Type	45A Double Pole Red Rocker + Neon + 13A Switched Socket
Insert Colour	Red+Bright Chrome/Black
EAN13 Barcode	5017503276707
Commodity Code	85363030
Luckins TSI	385555607
ETIM Class	EC000125
Dimensions(Nominal)	Double: Height = 88.0mm Width = 144.5mm Depth = 5.0mm
Weight	240 GR
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = N/A
Minimum Wall Box Depth	35mm
Switched Poles	Double
Current Rating	Switch 45 Amp Socket 13 Amp
Voltage	220/250V AC
Maximum Load	Switch 45 Amp Socket 13
Mains Frequency	50Hz
Mains Frequency IP Rating	50Hz IP2XD
IP Rating	IP2XD
IP Rating Contact Gap Minimum	IP2XD 3mm
IP Rating Contact Gap Minimum Terminal Capacity 1	IP2XD 3mm 3x6mm²
IP Rating Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2	IP2XD 3mm 3x6mm² 2x10mm²
IP Rating Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3	IP2XD 3mm 3x6mm² 2x10mm² 1x16mm²
IP Rating Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1	IP2XD 3mm 3x6mm² 2x10mm² 1x16mm² 3x6mm²
IP Rating Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2	IP2XD 3mm 3x6mm² 2x10mm² 1x16mm² 3x6mm² 2x10mm²
IP Rating Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3	IP2XD 3mm 3x6mm² 2x10mm² 1x16mm² 3x6mm² 2x10mm²
IP Rating Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Product Class 1 Ambient Operating	IP2XD 3mm 3x6mm² 2x10mm² 1x16mm² 3x6mm² 2x10mm² Must be earthed
IP Rating Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Product Class 1 Ambient Operating Temperature	IP2XD 3mm 3x6mm² 2x10mm² 1x16mm² 3x6mm² 2x10mm² Must be earthed -5° to +40°C
IP Rating Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation	IP2XD 3mm 3x6mm² 2x10mm² 1x16mm² 3x6mm² 2x10mm² Must be earthed -5° to +40°C Internal Use Only

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,