# DATASHEET


Hamilton<sup>®</sup> making connections beautifully

### Code: 774XTSBC-W

## Hartland | HARTLAND RANGE | Multi-Way Touch Slave Controllers

#### Product Image


#### Wiring



MASTER MODULE SLAVE MODULE SLAVE MODULE ONLY ONE MASTER MODULE IS USED PER CIRCUIT.

#### Dimensions





Insert Type	4 gang Multi-Way Touch Slave Controller
Insert Colour	Bright Chrome/White
EAN13 Barcode	5028690270454
Commodity Code	85363010
Luckins TSI	391565322
ETIM Class	EC000025
Dimensions(Nominal)	Double: Height = 88.0mm Width = 144.5mm Depth = 5.0mm
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = 106.5mm
Minimum Wall Box Depth	35mm
Switched Poles	N/A
Current Rating	The same as Touch Master or Ceiling Dimmer
Voltage	220/250V AC
Maximum Load	The same as Touch Master
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	N/A
Contact Gap Minimum Terminal Capacity 1	N/A 2x1mm²
-	
Terminal Capacity 1	2x1mm²
Terminal Capacity 1 Terminal Capacity 2	2x1mm <sup>2</sup> 2x1.5mm <sup>2</sup>
Terminal Capacity 1 Terminal Capacity 2 Earth Terminal Capacity 1	2x1mm <sup>2</sup> 2x1.5mm <sup>2</sup> 5x1mm <sup>2</sup>
Terminal Capacity 1 Terminal Capacity 2 Earth Terminal Capacity 1 Earth Terminal Capacity 2	2x1mm <sup>2</sup> 2x1.5mm <sup>2</sup> 5x1mm <sup>2</sup> 4 x 1.5mm2
Terminal Capacity 1Terminal Capacity 2Earth Terminal Capacity 1Earth Terminal Capacity 2Earth Terminal Capacity 3	2x1mm <sup>2</sup> 2x1.5mm <sup>2</sup> 5x1mm <sup>2</sup> 4 x 1.5mm2 3 x 2.5mm2
Terminal Capacity 1Terminal Capacity 2Earth Terminal Capacity 1Earth Terminal Capacity 2Earth Terminal Capacity 3Earth Terminal Capacity 4	2x1mm <sup>2</sup> 2x1.5mm <sup>2</sup> 5x1mm <sup>2</sup> 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand
Terminal Capacity 1Terminal Capacity 2Earth Terminal Capacity 1Earth Terminal Capacity 2Earth Terminal Capacity 3Earth Terminal Capacity 4Earth Terminal Capacity 5	2x1mm <sup>2</sup> 2x1.5mm <sup>2</sup> 5x1mm <sup>2</sup> 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2
Terminal Capacity 1Terminal Capacity 2Earth Terminal Capacity 1Earth Terminal Capacity 2Earth Terminal Capacity 3Earth Terminal Capacity 4Earth Terminal Capacity 5Product Class 1Ambient Operating	2x1mm <sup>2</sup> 2x1.5mm <sup>2</sup> 5x1mm <sup>2</sup> 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Face plate must be earthed
Terminal Capacity 1Terminal Capacity 2Earth Terminal Capacity 1Earth Terminal Capacity 2Earth Terminal Capacity 3Earth Terminal Capacity 4Earth Terminal Capacity 5Product Class 1Ambient Operating Temperature	2x1mm <sup>2</sup> 2x1.5mm <sup>2</sup> 5x1mm <sup>2</sup> 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Face plate must be earthed -5° to +40°C

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

**T:** +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.com (WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 19/05/2024 E&OE



## Code: 774XTSBC-W Hartland | HARTLAND RANGE | Multi-Way Touch Slave Controllers

Additional Notes	Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers
Patents And Trade Marks	Hartland is a Registered Trade Mark No. 2344778

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

**T:** +44 (0)1747 860088

**E:** info@hamilton-litestat.com | **W:** www.hamilton-litestat.com (WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 19/05/2024 E&OE