DATASHEET



2 gang 13A Single Pole Switched Socket with 45W Type A&C Quick Charge and Power Delivery

Code: 77CSS2USBPDBC-W

Hartland CFX | HARTLAND CFX RANGE | USB Power Sockets

Insert Type

Insert Colour

Product Image



 EAN13 Barcode
 5051164033927

 Commodity Code
 85363010

 ETIM Class
 EC000125

Dimensions(Nominal)Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm

Bright Chrome/White

Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips

3mm

Minimum Wall Box Depth 35mm

Switched Poles Single

Current Rating 5-20VDC 45W MAX available with type C connected

only 27W when both outlets used

Voltage 180/250V AC

Maximum Load 13A. USB 3A X2

Mains Frequency 50/60Hz

IP Rating IP2X

Contact Gap Minimum

Terminal Capacity 1 4x 1.5mm²

Terminal Capacity 2 3x 2.5mm²

Terminal Capacity 3 2x 4mm²
Earth Terminal Capacity 1 4x 1.5mm²

Earth Terminal Capacity 2 3x 2.5mm²

Earth Terminal Capacity 3 2x 4mm²

Product Class 1 Must be earthed

Ambient Operating $-5^{\circ}\text{C to } +40^{\circ}\text{C}$ **Temperature**

Recommended Location Indoors: Dry locations on

Maximum Installation 2000m Altitude

Standard/Approval BS1363 BS EN 62368

Patents And Trade MarksCFX is a Registered Trade Mark No 2398667 Hartland
CFX is a Registered Design under Reference Nos. R21

= 3023446 SS2 = 3023445

Dimensions

Wiring

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.cor

(\M/FR

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 04/05/2024 E&OE