DATASHEET



Code: 78SS1USBBK-B

Hartland | HARTLAND RANGE | USB Power Sockets


Product Image




Wiring

Wiring 13Amp Switched Single Sockets with USB Charging Outlet

Neutral ZEE Earth _____ Live



Dimensions



Insert Type	1 gang 13A Single Pole Switched Socket with 1 USB Outlet 1x2.1A
Insert Colour	Black Nickel/Black
EAN13 Barcode	5017504089078
Commodity Code	85363010
Luckins TSI	404387785
ETIM Class	EC000125
Dimensions(Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm
Weight	151 GR
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A
Minimum Wall Box Depth	35mm
Switched Poles	Single
Current Rating	13 Amp, USB 1 x 2.1A
Voltage	180/250V AC, USB = 5V
Maximum Load	13 Amp, USB = 2.1A
Mains Frequency	50/60Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Contact Gap Minimum Terminal Capacity 1	3mm 3x2.5mm ²
·	
Terminal Capacity 1	3x2.5mm²
Terminal Capacity 1 Terminal Capacity 2	3x2.5mm ² 3x4mm ²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3	3x2.5mm² 3x4mm² 2x6mm² Multi-Strand
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1	3x2.5mm² 3x4mm² 2x6mm² Multi-Strand 3x2.5mm²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2	3x2.5mm² 3x4mm² 2x6mm² Multi-Strand 3x2.5mm² 3x4mm²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3	3x2.5mm² 3x4mm² 2x6mm² Multi-Strand 3x2.5mm² 3x4mm² 2x6mm² Multi-Strand
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Product Class 1 Ambient Operating	3x2.5mm² 3x4mm² 2x6mm² Multi-Strand 3x2.5mm² 3x4mm² 2x6mm² Multi-Strand Must be earthed
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Product Class 1 Ambient Operating Temperature	3x2.5mm² 3x4mm² 2x6mm² Multi-Strand 3x2.5mm² 3x4mm² 2x6mm² Multi-Strand Must be earthed -15°C to +40°C
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation	3x2.5mm² 3x4mm² 2x6mm² Multi-Strand 3x2.5mm² 3x4mm² 2x6mm² Multi-Strand Must be earthed -15°C to +40°C Internal Use Only

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44(0)1747860088

E: info@hamilton-litestat.com|**W:** www.hamilton-litestat.cor

(W/FR

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 06/05/2024 ENG