
Code: 79C2J45B Hartland CFX | HARTLAND CFX RANGE | Telephone and Data Outlets

Product Image



Wiring




Pin		ule Colour Codes:	
No.	Schedule 568A	Schedule 568B	
1	WHITE / Green	WHITE / Orange	
2	GREEN / White	ORANGE / White	
23	WHITE / Orange	WHITE / Green	
4	BLUE / White	BLUE / White	
5	WHITE / Blue	WHITE / Blue	
6	ORANGE / White	GREEN / White	
7	WHITE / Brown	WHITE / Brown	
	BROWN / White	BROWN / White	
Main Wire Colour shown in CAPITALS			
Please always check with the			

colour coding found on the product.

RJ45 CAT5e and CAT6 Wiring Colour Codes

Dimensions



Insert Type	2 gang RJ45 CAT 5E Outlet - Unshielded
Insert Colour	Black
EAN13 Barcode	5017504291587
Commodity Code	85176990
Luckins TSI	388242001
ETIM Class	EC001264
Dimensions(Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm
Weight	110 GR
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	N/A
Current Rating	n/a
IP Rating	IP2XD
Contact Gap Minimum	N/A
Earth Terminal Capacity 1	5x1mm ²
Earth Terminal Capacity 2	4x1.5mm²
Earth Terminal Capacity 3	3x2.5mm ²
Earth Terminal Capacity 4	1 x 4mm² Multi-Strand
Earth Terminal Capacity 5	1x6mm²
Product Class 1	Must be earthed (ref BS7671 415.2.1)
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	N/A
Patents And Trade Marks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 =3023445

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.com (WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 18/05/2024 E&OE