## **DATASHEET**



Code: 79C2XLEDITB100

# Hartland CFX | HARTLAND CFX RANGE | LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmers

Product Image



| 1/1   | irir  |    |  |  |
|-------|-------|----|--|--|
| v v I | 11 11 | ıu |  |  |



#### Dimensions

| Insert Type               | 2 gang 100W LED Trailing/Leading Edge Push On/Off<br>Rotary 2 Way Switching Dimmer |  |  |  |
|---------------------------|--|--|--|--|
| Insert Colour             | Antique Brass  |  |  |  |
| EAN13 Barcode             | 5017504079697  |  |  |  |
| <b>Commodity Code</b>     | 85365015   |  |  |  |
| Luckins TSI               | 403372610  |  |  |  |
| ETIM Class                | EC000025   |  |  |  |
| Dimensions(Nominal)       | Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm                               |  |  |  |
| Weight                    | 240 GR   |  |  |  |
| Fixing Hole Centres       | Box Fixing = 60.3mm Grid Fixing = CFX Clips  |  |  |  |
| Minimum Wall Box Depth    | 35mm   |  |  |  |
| Switched Poles            | Single   |  |  |  |
| Current Rating            | 0.3A Per Gang  |  |  |  |
| Voltage                   | 230V AC  |  |  |  |
| Maximum Load              | 5-70W Per Gang   |  |  |  |
| Mains Frequency           | 50Hz   |  |  |  |
| IP Rating                 | IP2XD  |  |  |  |
| Terminal Capacity 1       | 2X1mm²   |  |  |  |
| Terminal Capacity 2       | 2X1.5mm²   |  |  |  |
| Earth Terminal Capacity 1 | 5x1mm²   |  |  |  |
| Earth Terminal Capacity 2 | 4X1.5mm²   |  |  |  |
| Earth Terminal Capacity 3 | 3X2.5mm²   |  |  |  |
| Earth Terminal Capacity 4 | 1X4mm² Multi-Strand  |  |  |  |
| Earth Terminal Capacity 5 | 1X6mm²   |  |  |  |
| Product Class 1           | Face plate must be earthed   |  |  |  |
| Ambient Operating         | -5°C to +40°C  |  |  |  |

Internal Use Only

BS EN 60669-2-1

Trailing Edge & Leading Edge Dimmer

2000m

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road Brislington Bristol BS4 5N7

T: +44 (0)1747 860088

E: info@hamilton-litestat.com|**W:** www.hamilton-litestat.cor

**Temperature** 

Altitude

**Recommended Location** 

**Maximum Installation** 

Standard/Approval
Additional Notes

(WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was energated on 15/05/2024 EXOF


### **DATASHEET**



Code: 79C2XLEDITB100

## Hartland CFX | HARTLAND CFX RANGE | LED Trailing/Leading Edge Push On/Off Rotary 2

**Way Switching Dimmers** 



**Patents And Trade Marks** 

CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445

**T:** +44 (0)1747 860088

: info@hamilton-litestat.com | W: www.hamilton-litestat.cor

(WFR)