# **DATASHEET**



Code: 79CEURO1

# Hartland CFX | HARTLAND CFX RANGE | EuroFix Apertured Plates complete with Fixing Grid


### **Product Image**



### Wiring



#### **Dimensions**



Insert Type	1 gang EuroFix 25x50mm Apertured Plate with Grid
Insert Colour	N/A
EAN13 Barcode	5017504299163
Commodity Code	74198090
Luckins TSI	391561012
ETIM Class	EC000018
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm
Weight	122 GR
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	As Per Insert
Switched Poles	N/A
Current Rating	Insert Specific
Voltage	Insert Specific
Maximum Load	Insert Specific
IP Rating	N/A
Contact Gap Minimum	N/A
Earth Terminal Capacity 1	5x1mm²
Earth Terminal Capacity 2	4x1.5mm²
Earth Terminal Capacity 3	3x2.5mm²
Earth Terminal Capacity 4	1x4mm² Multi-strand
Earth Terminal Capacity 5	1x6mm²
Product Class 1	Face plate must be earthed
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	N/A
Additional Notes	See EuroFix for a full range of inserts. Plates must be Earthed via the Earth Tag.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

**E:** info@hamilton-litestat.com|**W:** www.hamilton-litestat.con

(WFR

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 26/04/2024 ESOF.