## **DATASHEET**



Code: 79CEURO4

# Hartland CFX | HARTLAND CFX RANGE | EuroFix Apertured Plates complete with Fixing Grid


### **Product Image**



#### Wiring



#### Dimensions



Insert Type	4 gang EuroFix 100x50mm Apertured Plate with Grid
Insert Colour	N/A
EAN13 Barcode	5017504299187
Commodity Code	74198090
Luckins TSI	391561041
ETIM Class	EC000018
Dimensions(Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm
Weight	145 GR
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	As Per Inserts
Switched Poles	N/A
Current Rating	Insert Specific
Voltage	Insert Specific
Maximum Load	Insert Specific
IP Rating	N/A
IP Rating  Contact Gap Minimum	N/A N/A
_	
Contact Gap Minimum	N/A
Contact Gap Minimum  Earth Terminal Capacity 1	N/A 5x1mm²
Contact Gap Minimum  Earth Terminal Capacity 1  Earth Terminal Capacity 2	N/A 5x1mm² 4x1.5mm²
Contact Gap Minimum  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3	N/A  5x1mm²  4x1.5mm²  3x2.5mm²
Contact Gap Minimum  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4	N/A  5x1mm²  4x1.5mm²  3x2.5mm²  1x4mm² Multi-strand
Contact Gap Minimum  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 5	N/A  5x1mm²  4x1.5mm²  3x2.5mm²  1x4mm² Multi-strand  1x6mm²
Contact Gap Minimum  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1	N/A  5x1mm²  4x1.5mm²  3x2.5mm²  1x4mm² Multi-strand  1x6mm²  Face plate must be earthed
Contact Gap Minimum  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Recommended Location  Maximum Installation	N/A  5x1mm²  4x1.5mm²  3x2.5mm²  1x4mm² Multi-strand  1x6mm²  Face plate must be earthed  Internal Use Only
Contact Gap Minimum  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Recommended Location  Maximum Installation  Altitude	N/A  5x1mm²  4x1.5mm²  3x2.5mm²  1x4mm² Multi-strand  1x6mm²  Face plate must be earthed  Internal Use Only  2000m

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

**T:** +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.cor

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 20/05/2024 E&OE