DATASHEET




Code: 79CJ45B Hartland CFX | HARTLAND CFX RANGE | Telephone and Data Outlets

Product Image



Wiring




No	Schedule 568A	ule Colour Codes: Schedule 568B	
	WHITE / Green GREEN / White WHITE / Orange	WHITE / Orange ORANGE / White WHITE / Green	
45	BLUE / White WHITE / Blue	BLUE / White WHITE / Blue	
678	ORANGE / White WHITE / Brown BROWN / White	GREEN / White WHITE / Brown BROWN / White	
Main Wire Colour shown in CAPITALS			

colour coding found on the product.

RJ45 CAT5e and CAT6 Wiring Colour Codes

Dimensions



Insert Type	1 gang RJ45 CAT 5E Outlet - Unshielded
Insert Colour	Black
EAN13 Barcode	5017504291570
Commodity Code	85176990
Luckins TSI	388241989
ETIM Class	EC001264
Dimensions(Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm
Weight	129 GR
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	N/A
Current Rating	n/a
IP Rating	IP2XD
Contact Gap Minimum	N/A
Earth Terminal Capacity 1	5x1mm ²
Earth Terminal Capacity 2	4x1.5mm²
Earth Terminal Capacity 3	3x2.5mm ²
Earth Terminal Capacity 4	1 x 4mm² Multi-Strand
Earth Terminal Capacity 5	1x6mm²
Product Class 1	Must be earthed (ref BS7671 415.2.1)
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	N/A
Patents And Trade Marks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 =3023445

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.com (WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 18/05/2024 E&OE