


Code: 79CSPNAB-B  
Hartland CFX | HARTLAND CFX RANGE | Connection Units

Product Image



Wiring



Dimensions

Insert Type	1 gang 13A Double Pole Fused Spur + Neon
Insert Colour	Antique Brass/Black
EAN13 Barcode	5017504292928
Commodity Code	85369010
Luckins TSI	391561096
ETIM Class	EC001590
Dimensions(Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm
Weight	155 GR
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	Double
Current Rating	13 Amp
Voltage	220/250V AC
Maximum Load	13 Amp
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Terminal Capacity 1	3x2.5mm <sup>2</sup>
Terminal Capacity 2	2x4mm <sup>2</sup> Multi-Strand
Terminal Capacity 3	1x6mm <sup>2</sup>
Earth Terminal Capacity 1	6x1mm <sup>2</sup>
Earth Terminal Capacity 2	5x1.5mm <sup>2</sup>
Earth Terminal Capacity 3	3x2.5mm <sup>2</sup>
Earth Terminal Capacity 4	2x4mm <sup>2</sup> Multi-Strand
Earth Terminal Capacity 5	1x6mm <sup>2</sup>
Product Class 1	Must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS 1363-4

# DATASHEET


**Code:** 79CSPNAB-B

**Hartland CFX | HARTLAND CFX RANGE | Connection Units**

**Hamilton**<sup>®</sup>  
HARTLAND CFX  
SPN  
Switched Spur & Neon

## Patents And Trade Marks

CFX is a Registered Trade Mark No 2398667 Hartland  
CFX is a Registered Design under Reference Nos. R21  
= 3023446 SS2 =3023445



R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,  
4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

**T:** +44 (0)1747 860088

**E:** [info@hamilton-litestat.com](mailto:info@hamilton-litestat.com) | **W:** [www.hamilton-litestat.com](http://www.hamilton-litestat.com)

(WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 23/04/2024 E&OE