DATASHEET



Code: 7G21EURO2

Hartland G2 | HARTLAND G2 RANGE | EuroFix Apertured Plates complete with Fixing Grid


Product Image



Wiring



Dimensions



Insert Type	2 gang EuroFix 50x50mm Apertured Plate with Grid
Insert Colour	N/A
EAN13 Barcode	5051164024604
Commodity Code	73269098
Luckins TSI	423823589
ETIM Class	EC000018
Dimensions(Nominal)	Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm
Weight	87 GR
Fixing Hole Centres	Box Fixing = 60.3mm
Minimum Wall Box Depth	As Per Inserts
Switched Poles	N/A
Current Rating	Insert Specific
Voltage	Insert Specific
Maximum Load	Insert Specific
IP Rating	N/A
IP Rating Contact Gap Minimum	N/A N/A
_	
Contact Gap Minimum	N/A
Contact Gap Minimum Earth Terminal Capacity 1	N/A 5x1mm²
Contact Gap Minimum Earth Terminal Capacity 1 Earth Terminal Capacity 2	N/A 5x1mm² 4x1.5mm²
Contact Gap Minimum Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3	N/A 5x1mm² 4x1.5mm² 3x2.5mm²
Contact Gap Minimum Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4	N/A 5x1mm² 4x1.5mm² 3x2.5mm² 1x4mm² Multi-strand
Contact Gap Minimum Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5	N/A 5x1mm² 4x1.5mm² 3x2.5mm² 1x4mm² Multi-strand 1x6mm²
Contact Gap Minimum Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1	N/A 5x1mm² 4x1.5mm² 3x2.5mm² 1x4mm² Multi-strand 1x6mm² Face plate must be earthed
Contact Gap Minimum Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Recommended Location Maximum Installation	N/A 5x1mm² 4x1.5mm² 3x2.5mm² 1x4mm² Multi-strand 1x6mm² Face plate must be earthed Internal Use Only
Contact Gap Minimum Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Recommended Location Maximum Installation Altitude	N/A 5x1mm² 4x1.5mm² 3x2.5mm² 1x4mm² Multi-strand 1x6mm² Face plate must be earthed Internal Use Only 2000m

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.com

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 19/05/2024 E&OE