

**Code:** 7G21SS2USBPDPB-W

## Hartland G2 | HARTLAND G2 RANGE | USB Power Sockets

### Product Image



<b>Insert Type</b>	2 gang 13A Single Pole Switched Socket with 45W Type A&C Quick Charge and Power Delivery
<b>Insert Colour</b>	Polished Brass/White
<b>EAN13 Barcode</b>	5051164033521
<b>Commodity Code</b>	85363010
<b>ETIM Class</b>	EC000125
<b>Dimensions(Nominal)</b>	Double: Height = 87.4mm Width = 144.4mm Depth = 4.65mm
<b>Fixing Hole Centres</b>	Box Fixing = 120.6mm
<b>Minimum Wall Box Depth</b>	35mm
<b>Switched Poles</b>	Single
<b>Current Rating</b>	5-20VDC 45W MAX available with type C connected only 27W when both outlets used
<b>Voltage</b>	180/250V AC
<b>Maximum Load</b>	13A, USB 3A X2
<b>Mains Frequency</b>	50/60Hz
<b>IP Rating</b>	IP2X
<b>Contact Gap Minimum</b>	3mm
<b>Terminal Capacity 1</b>	4x 1.5mm <sup>2</sup>
<b>Terminal Capacity 2</b>	3x 2.5mm <sup>2</sup>
<b>Terminal Capacity 3</b>	2x 4mm <sup>2</sup>
<b>Earth Terminal Capacity 1</b>	4x 1.5mm <sup>2</sup>
<b>Earth Terminal Capacity 2</b>	3x 2.5mm <sup>2</sup>
<b>Earth Terminal Capacity 3</b>	2x 4mm <sup>2</sup>
<b>Product Class 1</b>	Must be earthed
<b>Ambient Operating Temperature</b>	-5°C to +40°C
<b>Recommended Location</b>	Indoors: Dry locations on
<b>Maximum Installation Altitude</b>	2000m
<b>Standard/Approval</b>	BS1363 BS EN 62368
<b>Patents And Trade Marks</b>	Hartland G2 is a Registered Trade Mark No UK00003388376

### Wiring

### Dimensions

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,  
4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

**T:** +44 (0)1747 860088

**E:** info@hamilton-litestat.com | **W:** www.hamilton-litestat.com

(WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 18/05/2024 E&OE