DATASHEET



Code: 7G24SS2USBPDSS-B

Hartland G2 | HARTLAND G2 RANGE | USB Power Sockets

Product Image



Insert Type	2 gang 13A Single Pole Switched Socket with 45W Type A&C Quick Charge and Power Delivery
Insert Colour	Satin Steel/Black
EAN13 Barcode	5051164033552
Commodity Code	85363010
ETIM Class	EC000125
Dimensions(Nominal)	Double: Height = 87.4mm Width = 144.4mm Depth = 4.65mm
Fixing Hole Centres	Box Fixing = 120.6mm
Minimum Wall Box Depth	35mm
Switched Poles	Single
Current Rating	5-20VDC 45W MAX available with type C connected only 27W when both outlets used
Voltage	180/250V AC
Maximum Load	13A, USB 3A X2
Mains Frequency	50/60Hz
IP Rating	IP2X
Contact Gap Minimum	3mm
Terminal Capacity 1	4x 1.5mm²
Terminal Capacity 2	3x 2.5mm²
Terminal Capacity 3	2x 4mm²
Earth Terminal Capacity 1	4x 1.5mm²
Earth Terminal Capacity 2	3x 2.5mm²
Earth Terminal Capacity 3	2x 4mm²
Product Class 1	Must be earthed
Ambient Operating Temperature	-5°C to +40°C
Recommended Location	Indoors: Dry locations on
Mar Carrie Landa Hallan	0000

Wiring

Dimensions

Maximum Installation 2000m
Altitude
Standard/Approval BS1363 BS EN 62368

Patents And Trade Marks Hartland G2 is a Registered Trade Mark No

UK00003388376

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

: info@hamilton-litestat.com | **W:** www.hamilton-litestat.cor

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 14/05/2024 E&OE