Code: 7G28SS2USBPDBK-B Hartland G2 | HARTLAND G2 RANGE | USB Power Sockets

Product Image	Insert Type	2 gang 13A Single Pole Switched Socket with 45W Type A&C Quick Charge and Power Delivery
	Insert Colour	Black Nickel/Black
	EAN13 Barcode	5051164033613
	Commodity Code	85363010
	ETIM Class	EC000125
	Dimensions(Nominal)	Double: Height = 87.4mm Width = 144.4mm Depth = 4.65mm
	Fixing Hole Centres	Box Fixing = 120.6mm
	Minimum Wall Box Depth	35mm
	Switched Poles	Single
	Current Rating	5-20VDC 45W MAX available with type C connected only 27W when both outlets used
	Voltage	180/250V AC
	Maximum Load	13A, USB 3A X2
	Mains Frequency	50/60Hz
	IP Rating	IP2X
	Contact Gap Minimum	3mm
	Terminal Capacity 1	4x 1.5mm²
	Terminal Capacity 2	3x 2.5mm²
	Terminal Capacity 3	2x 4mm²
	Earth Terminal Capacity 1	4x 1.5mm²
	Earth Terminal Capacity 2	3x 2.5mm²
	Earth Terminal Capacity 3	2x 4mm²
	Product Class 1	Must be earthed
	Ambient Operating Temperature	-5°C to +40°C
Wiring	Recommended Location	Indoors: Dry locations on
	Maximum Installation Altitude	2000m
Dimensions	Standard/Approval	BS1363 BS EN 62368
	Patents And Trade Marks	Hartland G2 is a Registered Trade Mark No UK00003388376

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ **T:** +44 (0)1747 860088

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.com (WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 14/05/2024 E&OE

Hamilton

making connections beautifully