DATASHEET



Code: 7G291X100LED

Hartland G2 | HARTLAND G2 RANGE | LED Trailing/Leading Edge Push On/Off Rotary Multi-Way Dimmers

way Dimmers		
Product Image	Item Long Description	
	Insert Type	1 gang 100W LED Trailing/Leading Edge Push On/Off Rotary Muilt-Way Dimmer
	Insert Colour	Antique Brass
	EAN13 Barcode	5051164002879
NO IMAGE	Commodity Code	85365015
	Luckins TSI	407518690
	ETIM Class	EC000025
	Dimensions(Nominal)	Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm
	Switched Poles	Single
Wiring	Current Rating	0.4A
NO IMAGE	Voltage	230V AC
	Maximum Load	5-100W in Trailing Edge / 5-75W in Leading Edge
	Mains Frequency	50Hz
	IP Rating	IP2XD
	Terminal Capacity 1	2X1mm²
	Terminal Capacity 2	2x1.5mm²
	Earth Terminal Capacity 1	5x1mm²
	Earth Terminal Capacity 2	4X1.5mm²
	Earth Terminal Capacity 3	3X2.5mm²
Dimensions	Earth Terminal Capacity 4	1X4mm² Multi-Strand
NO IMAGE	Earth Terminal Capacity 5	1X6mm²
	Product Class 1	Face plate muct be earthed
	Ambient Operating Temperature	-5°C to +40°C
	Recommended Location	Internal Use Only
	Maximum Installation Altitude	2000m
	Standard/Approval	BS EN 60669-2-1
	Additional Notes	Trailing Edge & Leading Edge Dimmer
	Patents And Trade Marks	Hartland G2 is a Registered Trade Mark No UK00003388376

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road Brislington Bristol BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com|**W:** www.hamilton-litestat.cor

(\M/FR

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This dataspeet was generated on 25/04/2024 FSOF.