DATASHEET




Code: 7G29C11AB-B

Hartland G2 | HARTLAND G2 RANGE | Hotel Card Switch with LED

Product Image



Wiring



Dimensions

Insert Type	1 gang 10A (6AX) Card Switch On/Off with Blue LED Locator
Insert Colour	Antique Brass/Black
EAN13 Barcode	5051164003098
Commodity Code	85363010
Luckins TSI	407519220
ETIM Class	EC000029
Dimensions(Nominal)	Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm
Fixing Hole Centres	Box Fixing = 60.3mm
Minimum Wall Box Depth	35mm
Switched Poles	Single
Current Rating	10A (6AX)
Voltage	220/250V AC
Maximum Load	10 Amp (6 Amp inductive)
Mains Frequency	50Hz
IP Rating	IP2XD
IP Rating Contact Gap Minimum	IP2XD 3mm
-	·· - ·-
Contact Gap Minimum	3mm
Contact Gap Minimum Terminal Capacity 1	3mm 3x1mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2	3mm 3x1mm² 2x1.5mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3	3mm 3x1mm² 2x1.5mm² 1x2.5mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed -5° to +40°C

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 25/04/2024 E&OE

DATASHEET



Code: 7G29C11AB-B

Hartland G2 | HARTLAND G2 RANGE | Hotel Card Switch with LED



Additional Notes Adjustable Time Delay 10 seconds - 5 minutes.

Suitable for 44mm and 54mm width Hotel Key Cards

Patents And Trade Marks Hartland G2 is a Registered Trade Mark No

UK00003388376

T: +44 (0)1747 860088

: info@hamilton-litestat.com | W: www.hamilton-litestat.con