DATASHEET




Code: 7G2AC11GA-QG

Hartland G2 | HARTLAND G2 RANGE | Hotel Card Switch with LED

Product Image



Wiring



Dimensions

_	
Insert Type	1 gang 10A (6AX) Card Switch On/Off with Blue LED Locator
Insert Colour	Anthra Gray/Quartz Grey
EAN13 Barcode	5051164028695
Commodity Code	85363010
Luckins TSI	433715593
ETIM Class	EC000029
Dimensions(Nominal)	Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm
Fixing Hole Centres	Box Fixing = 60.3mm
Minimum Wall Box Depth	35mm
Switched Poles	Single
Current Rating	10A (6AX)
Voltage	220/250V AC
Maximum Load	10 Amp (6 Amp inductive)
Mains Frequency	50Hz
IP Rating	IP2XD
IP Rating Contact Gap Minimum	IP2XD 3mm
-	
Contact Gap Minimum	3mm
Contact Gap Minimum Terminal Capacity 1	3mm 3x1mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2	3mm 3x1mm² 2x1.5mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3	3mm 3x1mm² 2x1.5mm² 1x2.5mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature	3mm 3x1mm² 2x1.5mm² 1x2.5mm² 5x1mm² 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed -5° to +40°C

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,

DATASHEET



Code: 7G2AC11GA-QG

Hartland G2 | HARTLAND G2 RANGE | Hotel Card Switch with LED



Additional Notes Adjustable Time Delay 10 seconds - 5 minutes.

Suitable for 44mm and 54mm width Hotel Key Cards

Patents And Trade Marks Hartland G2 is a Registered Trade Mark No

UK00003388376

T: +44 (0)1747 860088

: info@hamilton-litestat.com | W: www.hamilton-litestat.cor