DATASHEET



1 gang 200VA Inductive Leading Edge Push On/Off

Code: 7WC1X2VWH


Hartland CFX Colours | HARTLAND CFX COLOURS RANGE | Inductive Leading Edge Push On/Off Rotary 2 Way Switching Dimmers

Insert Type

ETIM Class

Product Image

Wiring



	Rotary 2 Way Switching Dimmer
Insert Colour	White
EAN13 Barcode	5017504006044
Commodity Code	85365015
Luckins TSI	394188984

Dimensions(Nominal) Single: Height = 86.0mm Width = 86.0mm Depth =

Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Push

EC000025

Minimum Wall Box Depth 35mm **Switched Poles** Single

Current Rating 0.8 Amp

220/250V AC Voltage

Maximum Load 200VA (low voltage) Min Load 25VA

Mains Frequency 50Hz IP2XD **IP Rating**

None **Contact Gap Minimum Terminal Capacity 1** 2x1mm²

2x1.5mm² **Terminal Capacity 2**

Earth Terminal Capacity 1 5x1mm²

Earth Terminal Capacity 2 4 x 1.5mm2

Earth Terminal Capacity 3 1 x 4mm2 Multi-strand **Earth Terminal Capacity 4**

Earth Terminal Capacity 5 1 x 6mm2

Product Class 1 Face plate must be earthed

3 x 2.5mm2


Ambient Operating -5° to +40°C **Temperature**

Recommended Location Internal Use Only

Maximum Installation 2000m Altitude

Standard/Approval BS EN 60669-1

Dimensions



R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

All accessories are manufactured under an accredited BS EN ISO 9001:2015
Quality Management System. It is the policy of the company to improve
products as part of our development programme. Therefore, we reserve
the right to alter designs and dimensions without prior notice. Illustrations

DATASHEET



Code: 7WC1X2VWH

Hartland CFX Colours | HARTLAND CFX COLOURS RANGE | Inductive Leading Edge Push On/Off Rotary 2 Way Switching Dimmers

Additional Notes

LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE:It is recommended to contact the

manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load.

Patents And Trade Marks

CFX is a Registered Trade Mark No 2398667

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 18/04/2024/ENG.