DATASHEET



Code: 82CSS2USBULTSB-W

Sheer CFX | SHEER CFX RANGE | USB Power Sockets


Product Image



Wiring



Dimensions



Insert Type	2 gang 13A Double Pole Switched Socket with 2 USB Outlets 2x2.4A (4.8A Total)
Insert Colour	Satin Brass/White
EAN13 Barcode	5017504090401
Commodity Code	85363010
Luckins TSI	405689220
ETIM Class	EC000125

Dimensions(Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 1.5mm plate + 3.0mm gasket

Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips

Minimum Wall Box Depth 35mm **Switched Poles** Double

Current Rating 13 Amp, USB 2 x 2.4A

180/250V AC USB = 5V Voltage

Maximum Load 13 Amp, USB = 2.4A X 2

50/60Hz Mains Frequency IP2XD

Contact Gap Minimum 3_{mm}

3x2.5mm² Terminal Capacity 1

3x4mm² **Terminal Capacity 2**

Terminal Capacity 3 2x6mm² Multi-Strand

Earth Terminal Capacity 1 3x2.5mm²

3x4mm² **Earth Terminal Capacity 2**

2x6mm² Multi-Strand Earth Terminal Capacity 3

Product Class 1 Must be earthed

-15°C to +40°C Ambient Operating **Temperature**

Recommended Location Internal Use Only

Maximum Installation 2000m

Altitude

IP Rating

Standard/Approval BS1363 BS EN 62368

Patents And Trade Marks CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design

under Reference Nos. R21 = 3020754 SS2 = 3020755

4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

Il accessories are manufactured under an accredited BS EN ISO 9001:2015 pullity Management System. It is the policy of the company to improve roducts as part of our development programme. Therefore, we reserve he right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and rinting process and are not binding. Due to manufacturing processes we annot guarantee an exact colour match and shadings of certain finishes. his datasheet was generated on 29/04/2024 E&OE