DATASHEET



Code: 84SS1USBSS-B


Sheer | SHEER RANGE | USB Power Sockets

Product Image




Wiring

Wiring 13Amp Switched Single Sockets with USB Charging Outlet ■ Neutral 🗷 Earth 🗆



Dimensions



Insert Type	1 gang 13A Single Pole Switched Socket with 1 USB Outlet 1x2.1A
Insert Colour	Satin Steel/Black
EAN13 Barcode	5017504089528
Commodity Code	85363010
Luckins TSI	404388700
ETIM Class	EC000125
Dimensions(Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A
Minimum Wall Box Depth	35mm
Switched Poles	Single
Current Rating	13 Amp, USB 1 x 2.1A
Voltage	180/250V AC, USB = 5V
Maximum Load	13 Amp, USB = 2.1A
Mains Frequency	50/60Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Terminal Capacity 1	3x2.5mm²
Terminal Capacity 2	3x4mm²
Terminal Capacity 3	2x6mm² Multi-Strand
Earth Terminal Capacity 1	3x2.5mm²
Earth Terminal Capacity 2	3x4mm²
Earth Terminal Capacity 3	2x6mm² Multi-Strand
Product Class 1	Must be earthed
Ambient Operating Temperature	-15°C to +40°C
Recommended Location	Internal Use Only
Maximum Installation	2000m

BS1363 BS EN 62368

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,

Altitude

Standard/Approval

Patents And Trade Marks

Sheer is a Registered Trade Mark No. 2296586