DATASHEET




Code: 89CSS1AB-B

Sheer CFX | SHEER CFX RANGE | Power Sockets

Product Image



Wiring



Dimensions

Insert Type	1 gang 13A Double Pole Switched Socket
Insert Colour	Antique Brass/Black
EAN13 Barcode	5017504062019
Commodity Code	85363010
Luckins TSI	387385749
ETIM Class	EC000125
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket
Weight	171 GR
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	Double
Current Rating	13 Amp
Voltage	220/250V AC
Maximum Load	13 Amp
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Contact Gap Minimum Terminal Capacity 1	3mm 4x2.5mm ²
Terminal Capacity 1	4x2.5mm²
Terminal Capacity 1 Terminal Capacity 2	4x2.5mm² 3x4mm²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3	4x2.5mm² 3x4mm² 2x6mm² Multi-Strand
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4	4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1	4x2.5mm ² 3x4mm ² 2x6mm ² Multi-Strand 1x10mm ² 4x2.5mm ²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2	4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm² 4x2.5mm² 3x4mm²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3	4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm² 4x2.5mm² 3x4mm² 2x6mm² Multi-Strand
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4	4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm² 4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Product Class 1 Ambient Operating	4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm² 4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm² Must be earthed
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Product Class 1 Ambient Operating Temperature	4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm² 4x2.5mm² 3x4mm² 2x6mm² Multi-Strand 1x10mm² Must be earthed -5° to +40°C

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.cor

(WFR)


All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 28/03/2024 EXOF.

DATASHEET



Code: 89CSS1AB-B

Sheer CFX | SHEER CFX RANGE | Power Sockets



Additional Notes Dual Earth: Yes

Patents And Trade Marks

CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755