DATASHEET




Code: 89DUS2B

Sheer Floor Sockets | SHEER FLOOR SOCKETS RANGE | Power Sockets


Product Image



Wiring



Dimensions



Insert Type	1 gang 2A Unswitched Socket
Insert Colour	Black
EAN13 Barcode	5017504035280
Commodity Code	85363010
Luckins TSI	398360151
ETIM Class	EC000125
Dimensions(Nominal)	Single: Height = 93.5mm Width = 85.5mm Depth = 3.0mm (6.5mm Hinged Cover)
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A
Minimum Wall Box Depth	35mm
Switched Poles	None
Current Rating	2 Amp
Voltage	220/250V AC
Maximum Load	2 Amp
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	None
Terminal Capacity 1	5 x1mm²
Terminal Capacity 2	4x1.5mm²
Terminal Capacity 3	2x2.5mm²
Terminal Capacity 4	1x4mm²
Earth Terminal Capacity 1	5x1mm²
Earth Terminal Capacity 2	4 x 1.5mm2
Earth Terminal Capacity 3	2 x 2.5mm2
Earth Terminal Capacity 4	1 x 4mm2
Product Class 1	Must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS 546
Additional Notes	Shuttered: Yes

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44(0)1747860088

E: info@hamilton-litestat.com|**W:** www.hamilton-litestat.con

(WFR)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 25/04/2024 E&OE