DATASHEET




Code: 89SPAB-B

Sheer | SHEER RANGE | Connection Units

Product Image



Wiring



Dimensions



Insert Type	1 gang 13A Double Pole Fused Spur
Insert Colour	Antique Brass/Black
EAN13 Barcode	5017503892907
Commodity Code	85369010
Luckins TSI	386905968
ETIM Class	EC001590
Dimensions(Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm
Weight	160 GR
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A
Minimum Wall Box Depth	35mm
Switched Poles	Double
Current Rating	13 Amp
Voltage	220/250V AC
Maximum Load	13 Amp
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Contact Gap Minimum Terminal Capacity 1	3mm 3x2.5mm²
-	-
Terminal Capacity 1	3x2.5mm²
Terminal Capacity 1 Terminal Capacity 2	3x2.5mm² 2x4mm² Multi-Strand
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3	3x2.5mm² 2x4mm² Multi-Strand 1x6mm²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1	3x2.5mm² 2x4mm² Multi-Strand 1x6mm² 6x1mm²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2	3x2.5mm² 2x4mm² Multi-Strand 1x6mm² 6x1mm² 5x1.5mm²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3	3x2.5mm² 2x4mm² Multi-Strand 1x6mm² 6x1mm² 5x1.5mm² 3x2.5mm²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4	3x2.5mm² 2x4mm² Multi-Strand 1x6mm² 6x1mm² 5x1.5mm² 3x2.5mm² 2 x 4mm2 Multi-strand
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5	3x2.5mm² 2x4mm² Multi-Strand 1x6mm² 6x1mm² 5x1.5mm² 3x2.5mm² 2 x 4mm2 Multi-strand 1x6mm²
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating	3x2.5mm² 2x4mm² Multi-Strand 1x6mm² 6x1mm² 5x1.5mm² 3x2.5mm² 2 x 4mm2 Multi-strand 1x6mm² Must be earthed
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature	3x2.5mm² 2x4mm² Multi-Strand 1x6mm² 6x1mm² 5x1.5mm² 3x2.5mm² 2 x 4mm2 Multi-strand 1x6mm² Must be earthed -5° to +40°C

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

L: info@hamilton-litestat.com|**W:** www.hamilton-litestat.cor

(WFR

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 24/04/2024 EXOE

DATASHEET



Code: 89SPAB-B

Sheer | SHEER RANGE | Connection Units

Patents And Trade Marks

Sheer is a Registered Trade Mark No. 2296586