# **DATASHEET**




Code: 89T21

### Sheer | SHEER RANGE | Toggle Switches

### **Product Image**



#### Wiring



### Dimensions

Insert Type	1 gang 20AX 2 Way Toggle
Insert Colour	Antique Brass
EAN13 Barcode	5028690892854
Commodity Code	85363030
Luckins TSI	386905861
ETIM Class	EC001590
Dimensions(Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm
Weight	147 GR
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A
Minimum Wall Box Depth	35mm
Switched Poles	Single
Current Rating	20AX
Voltage	220/250V AC
Maximum Load	20 Amp inductive
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Terminal Capacity 1	5x1mm²
Terminal Capacity 2	4x1.5mm²
Terminal Capacity 3	2x2.5mm²
Terminal Capacity 4	2x4mm² Multi-strand
<b>Terminal Capacity 5</b>	1x6mm²
Earth Terminal Capacity 1	6x1mm²
Earth Terminal Capacity 2	5x1.5mm²
Earth Terminal Capacity 3	3x2.5mm²
Earth Terminal Capacity 4	2x4mm² Multi-strand
Earth Terminal Capacity 5	1x6mm²
Product Class 1	Must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

**E:** info@hamilton-litestat.com|**W:** www.hamilton-litestat.cor

(WFR)


All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 19/04/2024 FXOF

# **DATASHEET**



**Code:** 89T21

# Sheer | SHEER RANGE | Toggle Switches



Maximum Installation 2000m

Altitude

Standard/Approval BS EN 60669-1

Patents And Trade Marks Sheer is a Registered Trade Mark No. 2296586