DATASHEET



Code: 89TCMB

Sheer | SHEER RANGE | Telephone and Data Outlets

Product Image




Wiring

Pin No.	BT Wiring Schedule Colour Codes: Striped Wires	
\Box	GREEN / White	
2	BLUE / White	
3	ORANGE / White	
4	WHITE / Orange	
5	WHITE / Blue	
6	WHITE / Green	
Main Wire Colour shown in CAPITALS		

Incoming Telephone Cable On 4 wire systems, Pin 1 and 6 are not connected.

The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected in parallel. ie Pin 1 to Pin 1; Pin 2 to Pin 2; etc. as shown in the diagram above.

Dimensions



Insert Type	1 gang Telephone Master
Insert Colour	Black
EAN13 Barcode	5017503891641
Commodity Code	85176990
Luckins TSI	386906006
ETIM Class	EC000018
Dimensions(Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm
Weight	120 GR
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A
Minimum Wall Box Depth	25mm
Switched Poles	N/A
Current Rating	n/a
IP Rating	IP2XD
Contact Gap Minimum	N/A
Earth Terminal Capacity 1	5x1mm²
Earth Terminal Capacity 2	4 x 1.5mm2
Earth Terminal Capacity 3	3 x 2.5mm2
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand
Earth Terminal Capacity 5	1 x 6mm2
Product Class 1	Must be earthed (ref BS7671 415.2.1)
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS 6312:2:2
Patents And Trade Marks	Sheer is a Registered Trade Mark No. 2296586

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.cor

1: +44 (0)1/4/86008

All accessories are manufactured under an accredited by EN ISO 9001:2015
Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.

This dataspeet was generated on 28/03/2024 ESOF.