Code: 8G21SPNPB-B Sheer G2 | SHEER G2 RANGE | Connection Units


Insert Type

Insert Colour

Product Image	
---------------	--



Wiring



EAN13 Barcode	5017504105075
Commodity Code	85369010
Luckins TSI	435715986
ETIM Class	EC001590
Dimensions(Nominal)	Single: Height = 85mm Width = 85mm Depth = 1.5mm + 2.7mm Gasket
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	As Per Inserts
Switched Poles	Double
Current Rating	13 Amp
Voltage	220/250V AC
Maximum Load	13 Amp
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Terminal Capacity 1	3x2.5mm ²
Terminal Capacity 2	2x4mm² Multi-Strand
Terminal Capacity 3	1x6mm²
Earth Terminal Capacity 1	6x1mm²
Earth Terminal Capacity 2	5x1.5mm²
Earth Terminal Capacity 3	3x2.5mm ²
Earth Terminal Capacity 4	2x4mm² Multi-Strand
Earth Terminal Capacity 5	1x6mm²
Product Class 1	Must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS 1363-4
Patents And Trade Marks	Sheer G2 is a Registered Trade Mark No XXXXXX

Dimensions

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.com (WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 06/05/2024 E&OE

Hamilton

making connections beautifully

1 gang 13A Double Pole Fused Spur + Neon

Polished Brass/Black