DATASHEET



Code: 8G24SS1USBSS-QG

Sheer G2 | SHEER G2 RANGE | USB Power Sockets


Product Image



Wiring

Wiring 13Amp Switched Single Sockets with USB Charging Outlet

Neutral ZZZ Earth _____ Live



Dimensions

Insert Type	1 gang 13A Single Pole Switched Socket with 1 USB Outlet 1x2.1A
Insert Colour	Satin Steel/Quartz Grey
EAN13 Barcode	5051164034238
Commodity Code	85363010
Luckins TSI	435712536
ETIM Class	EC000125
Dimensions(Nominal)	Single: Height = 85mm Width = 85mm Depth = 1.5mm + 2.7mm Gasket
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	Single
Current Rating	13 Amp, USB 1 x 2.1A
Voltage	180/250V AC, USB = 5V
Maximum Load	13 Amp, USB = 2.1A
Mains Frequency	50/60Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Terminal Capacity 1	3x2.5mm²
Terminal Capacity 2	3x4mm²
Terminal Capacity 3	2x6mm² Multi-Strand
Earth Terminal Capacity 1	3x2.5mm²
Earth Terminal Capacity 2	3x4mm²
Earth Terminal Capacity 3	2x6mm² Multi-Strand
Product Class 1	Must be earthed
Ambient Operating Temperature	-15°C to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS1363 BS EN 62368
Patents And Trade Marks	Sheer G2 is a Registered Trade Mark No XXXXXX

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.com

(WFR