DATASHEET



Code: 8G2EB1XLEDITB100

Sheer G2 | SHEER G2 RANGE | LED Trailing/Leading Edge Push On/Off Rotary 2 Way

ETIM Class

Switching Dimmers

Product Image



Insert Type	1 gang 100W LED Trailing/Leading Edge Push On/Off
	Rotary 2 Way Switching Dimmer

Insert Colour Etrium Bronze EAN13 Barcode 5017504098063

Commodity Code 85365015

Luckins TSI 435715973

Dimensions(Nominal) Single: Height = 85mm Width = 85mm Depth =

1.5mm + 2.7mm Gasket

Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips

5x1mm²

4X1.5mm²

EC000025

Minimum Wall Box Depth 35mm

Switched Poles Single

Current Rating 0.4A

230V AC Voltage

Maximum Load 5-100W (10 LED Lamps MAX)

Mains Frequency 50Hz

IP2XD **IP Rating**

2X1mm² **Terminal Capacity 1**

2x1.5mm² Terminal Capacity 2

Earth Terminal Capacity 1

Earth Terminal Capacity 3 3X2.5mm²

1X4mm² Multi-Strand **Earth Terminal Capacity 4**

1X6mm² Earth Terminal Capacity 5

Product Class 1 Face plate must be earthed

-5°C to +40°C **Ambient Operating**

Temperature

Earth Terminal Capacity 2

Recommended Location Internal Use Only

Maximum Installation 2000m

Altitude

BS EN 60669-2-1 Standard/Approval

Additional Notes Trailing Edge & Leading Edge Dimmer

Patents And Trade Marks Sheer G2 is a Registered Trade Mark No XXXXXX

Wiring



Dimensions

4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 04/05/2024 E&OE