DATASHEET




Code: 8G2MBDPNBL-B

Sheer G2 | SHEER G2 RANGE | Double Pole Switches

Product Image



Wiring



Dimensions

Insert Type	1 gang 20AX Double Pole Rocker + Neon
Insert Colour	Black/Black
EAN13 Barcode	5017504098735
Commodity Code	85363030
Luckins TSI	435716817
ETIM Class	EC001590
Dimensions(Nominal)	Single: Height = 85mm Width = 85mm Depth =
Differisions(Norminal)	1.5mm + 2.7mm Gasket
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	25mm
Switched Poles	Double
Current Rating	20AX
Voltage	220/250V AC
Maximum Load	20 Amp inductive
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Terminal Capacity 1	3x2.5mm²
Terminal Capacity 2	2x4mm² Multi-strand
Terminal Capacity 2 Terminal Capacity 3	2x4mm ² Multi-strand 1x6mm ²
Terminal Capacity 3	1x6mm²
Terminal Capacity 3 Earth Terminal Capacity 1	1x6mm² 6x1mm²
Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2	1x6mm² 6x1mm² 5x1.5mm²
Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3	1x6mm ² 6x1mm ² 5x1.5mm ² 3x2.5mm ²
Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4	1x6mm² 6x1mm² 5x1.5mm² 3x2.5mm² 2x4mm² Multi-strand
Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5	1x6mm² 6x1mm² 5x1.5mm² 3x2.5mm² 2x4mm² Multi-strand 1x6mm²
Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating	1x6mm² 6x1mm² 5x1.5mm² 3x2.5mm² 2x4mm² Multi-strand 1x6mm² Must be earthed
Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature	1x6mm² 6x1mm² 5x1.5mm² 3x2.5mm² 2x4mm² Multi-strand 1x6mm² Must be earthed -5° to +40°C
Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation	1x6mm² 6x1mm² 5x1.5mm² 3x2.5mm² 2x4mm² Multi-strand 1x6mm² Must be earthed -5° to +40°C Internal Use Only

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.com

(M/FR

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 03/05/2024 EXOF