### DATASHEET




Code: 911XTMAB-B

# Cheriton Georgian | CHERITON GEORGAIN RANGE | Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmers

Product Image

Wiring



Insert Type	1 gang 250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmer
Insert Colour	Antique Brass/Black
EAN13 Barcode	5028690361381
<b>Commodity Code</b>	85363010
Luckins TSI	391566787
ETIM Class	EC000025

**Dimensions(Nominal)**Single: Height = 88.0mm Width = 88.0mm Depth =

Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = 49.2mm

IP2XD

Minimum Wall Box Depth 35mm

Switched Poles N/A

Current Rating 1.1 Amp

Voltage 220/250V AC

Maximum Load 25W/25VA 250W Resistive 210VA Inductive Min Load 25W/25VA

Mains Frequency 50Hz

\_ \_ \_ \_ ...

Contact Gap Minimum N/A

Terminal Capacity 1 2x1mm<sup>2</sup>

Terminal Capacity 2 2x1.5mm<sup>2</sup>

Earth Terminal Capacity 1 5x1mm<sup>2</sup>

Earth Terminal Capacity 2 4 x 1.5mm2

Earth Terminal Capacity 3 3 x 2.5 mm2

Earth Terminal Capacity 4 1 x 4mm2 Multi-strand

Earth Terminal Capacity 5 1 x 6mm2

Product Class 1 Face plate must be earthed

Ambient Operating -5° to +40°C

Temperature

**IP Rating** 


**Recommended Location** Internal Use Only

Maximum Installation 2000m

Altitude

Standard/Approval BS EN 60669-2-1

#### Dimensions



R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.com

(WFR

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 23/04/2024 EXOE

### **DATASHEET**



Code: 911XTMAB-B

## Cheriton Georgian | CHERITON GEORGAIN RANGE | Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmers

#### **Additional Notes**

TRAILING EDGE TECHNOLOGY DIMMERS. Are suitable for control of both resistive and inductive loads. When used for dimming low voltage electronic halogen transformers it must be noted that the dimmer controls the primary side of the transformer. Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. When using mains voltage halogen load transformer - maximum rating is 210VA. NOTE: For multi-way switching a push to make retractive switch should be installed in the other positions. (Note:standard two way switches will not work with this product)

**Patents And Trade Marks** 

Cheriton is a Registered Trade Mark No. 2344779