# **DATASHEET**




Code: 91TVB

# Cheriton Georgian | CHERITON GEORGAIN RANGE | Television Coaxial Sockets


#### **Product Image**



### Wiring



### **Dimensions**



Insert Type	1 gang Non-Isolated TV 1in/1out
Insert Colour	Black
EAN13 Barcode	5017503361601
Commodity Code	85367000
Luckins TSI	385563136
ETIM Class	EC000439
Dimensions(Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 10.5mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A
Minimum Wall Box Depth	25mm
Switched Poles	N/A
Current Rating	n/a
IP Rating	IP2XD
Contact Gap Minimum	N/A
Contact Gap Minimum  Earth Terminal Capacity 1	N/A 5x1mm²
·	
Earth Terminal Capacity 1	5x1mm²
Earth Terminal Capacity 1 Earth Terminal Capacity 2	5x1mm <sup>2</sup> 4 x 1.5mm2
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3	5x1mm <sup>2</sup> 4 x 1.5mm2 3 x 2.5mm2
Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4	5x1mm <sup>2</sup> 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5	5x1mm <sup>2</sup> 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating	5x1mm <sup>2</sup> 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed (ref BS7671 415.2.1)
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature	5x1mm <sup>2</sup> 4 x 1.5mm2  3 x 2.5mm2  1 x 4mm2 Multi-strand  1 x 6mm2  Must be earthed (ref BS7671 415.2.1)  -5° to +40°C
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation	5x1mm <sup>2</sup> 4 x 1.5mm2  3 x 2.5mm2  1 x 4mm2 Multi-strand  1 x 6mm2  Must be earthed (ref BS7671 415.2.1)  -5° to +40°C  Internal Use Only
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation Altitude	5x1mm <sup>2</sup> 4 x 1.5mm2  3 x 2.5mm2  1 x 4mm2 Multi-strand  1 x 6mm2  Must be earthed (ref BS7671 415.2.1)  -5° to +40°C  Internal Use Only  2000m

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,