

**Code:** ELM1MODGY

**Elemento IP | ELEMENTO RANGE | IP66 Enclosures**

## Product Image




## Wiring



## Dimensions

**Hamilton®**  
ELEMENTO  
TRD-ELM-1MOD  
1 Module Enclosure



<b>Insert Type</b>	1 Module Enclosure
<b>Insert Colour</b>	No Insert Colour
<b>EAN13 Barcode</b>	5017503940462
<b>Commodity Code</b>	39206100
<b>Luckins TSI</b>	406102887
<b>Dimensions(Nominal)</b>	Single-Mod: Height = 153.0mm Width = 110.0mm Depth = 95.0mm
<b>Weight</b>	393 GR
<b>Fixing Hole Centres</b>	Box Fixing = 60.3mm Grid Fixing = N/A
<b>Switched Poles</b>	None
<b>Current Rating</b>	n/a
<b>IP Rating</b>	IP66
<b>Earth Terminal Capacity 1</b>	4x2.5mm <sup>2</sup>
<b>Earth Terminal Capacity 2</b>	3x4mm <sup>2</sup>
<b>Earth Terminal Capacity 3</b>	2x6mm <sup>2</sup> Multi-Strand
<b>Earth Terminal Capacity 4</b>	1x1mm <sup>2</sup>
<b>Product Class 1</b>	Must be earthed
<b>Ambient Operating Temperature</b>	-5° to +40°C
<b>Maximum Installation Altitude</b>	2000m
<b>Standard/Approval</b>	IP66
<b>Additional Notes</b>	4 Conduit entry points for 20mmØ drill out positions

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,  
4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: [info@hamilton-litestat.com](mailto:info@hamilton-litestat.com) | W: [www.hamilton-litestat.com](http://www.hamilton-litestat.com)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. This datasheet was generated on 3/30/2023 11:37:53 PM E&OE