DATASHEET



Code: HM2031

Verve | LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmers

Product Image



Wiring



Dimensions



Dimensional drawing is not available

Insert Type	1 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer
Insert Colour	White
EAN13 Barcode	5052750550194
Commodity Code	85365015
Luckins TSI	434147801
ETIM Class	EC000025
Dimensions(Nominal)	Single: Height = 86.7mm Width = 86.7mm Depth = 10.0mm
Weight	75 GR
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A
Minimum Wall Box Depth	35mm
Switched Poles	Single
Current Rating	0.4A
Voltage	230V AC
Maximum Load	5-100W (10 LED Lamps MAX)
Mains Frequency	50Hz
Mains Frequency IP Rating	50Hz IP2XD
IP Rating	IP2XD
IP Rating Terminal Capacity 1	IP2XD 2X1mm²
IP Rating Terminal Capacity 1 Terminal Capacity 2	IP2XD 2X1mm² 2x1.5mm²
IP Rating Terminal Capacity 1 Terminal Capacity 2 Earth Terminal Capacity 1	IP2XD 2X1mm² 2x1.5mm² 5x1mm²
IP Rating Terminal Capacity 1 Terminal Capacity 2 Earth Terminal Capacity 1 Earth Terminal Capacity 2	IP2XD 2X1mm² 2x1.5mm² 5x1mm² 4X1.5mm²
IP Rating Terminal Capacity 1 Terminal Capacity 2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2	IP2XD 2X1mm² 2x1.5mm² 5x1mm² 4X1.5mm² 3X2.5mm²
IP Rating Terminal Capacity 1 Terminal Capacity 2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4	IP2XD 2X1mm² 2x1.5mm² 5x1mm² 4X1.5mm² 3X2.5mm² 1X4mm² Multi-Strand
IP Rating Terminal Capacity 1 Terminal Capacity 2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5	IP2XD 2X1mm² 2x1.5mm² 5x1mm² 4X1.5mm² 3X2.5mm² 1X4mm² Multi-Strand 1X6mm²
IP Rating Terminal Capacity 1 Terminal Capacity 2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating	IP2XD 2X1mm² 2x1.5mm² 5x1mm² 4X1.5mm² 3X2.5mm² 1X4mm² Multi-Strand 1X6mm² Face plate must be earthed
IP Rating Terminal Capacity 1 Terminal Capacity 2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature	IP2XD 2X1mm² 2x1.5mm² 5x1mm² 4X1.5mm² 3X2.5mm² 1X4mm² Multi-Strand 1X6mm² Face plate must be earthed -5°C to +40°C
IP Rating Terminal Capacity 1 Terminal Capacity 2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation	IP2XD 2X1mm² 2x1.5mm² 5x1mm² 4X1.5mm² 3X2.5mm² 1X4mm² Multi-Strand 1X6mm² Face plate must be earthed -5°C to +40°C Internal Use Only

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road Brislington Bristol BS4 5N7

T: +44 (0)1747 860088

E: info@hamilton-litestat.com|**W:** www.hamilton-litestat.com

(WFR

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 24/04/2024 EXOE