## DATASHEET

Hamilton<sup>®</sup> making connections beautifully

## Code: HM2073 Verve || Connection Units

## Product Image



Wiring



Dimensions



Dimensional drawing is not available

Insert Type	1 gang 13A Double Pole Fused Spur
Insert Colour	White
EAN13 Barcode	5052750550392
Commodity Code	85369010
Luckins TSI	434147924
ETIM Class	EC001590
Dimensions(Nominal)	Single: Height = 86.7mm Width = 86.7mm Depth = 10.0mm
Weight	112 GR
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A
Minimum Wall Box Depth	35mm
Switched Poles	Single
Current Rating	13 Amp
Voltage	220/250V AC
Maximum Load	13 Amp
Contact Gap Minimum	3mm
Terminal Capacity 1	3x2.5mm <sup>2</sup>
Terminal Capacity 2	2x4mm <sup>2</sup> Multi-Strand
Terminal Capacity 3	1x6mm²
Terminal Capacity 4	6x1mm²
Earth Terminal Capacity 1	5x1.5mm²
Earth Terminal Capacity 2	3x2.5mm²
Earth Terminal Capacity 3	2x4mm <sup>2</sup>
Earth Terminal Capacity 4	1x6mm²
Product Class 1	Must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS 1363-4

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

**T:** +44 (0)1747 860088

**E:** info@hamilton-litestat.com | **W:** www.hamilton-litestat.com (WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 25/04/2024 E&OE