
Code: IDHF10VWH GRID-IT | GRID-IT RANGE | High Frequency Ballast Controller Module


Product Image



Wiring



Dimensions



Insert Type	1-10v DC High Frequency Ballast Controller Module (No Off)
Insert Colour	White/White
EAN13 Barcode	5051164009342
Commodity Code	85365015
Luckins TSI	391567744
Dimensions(Nominal)	Module: Height = Width = Depth =
Weight	29 GR
Switched Poles	N/A
Current Rating	n/a
Voltage	1-10V
Maximum Load	N/A
IP Rating	IP2XD
Contact Gap Minimum	3mm
Terminal Capacity 1	2x1mm²
Terminal Capacity 2	2x1.5mm²
Earth Terminal Capacity 1	5x1mm²
Earth Terminal Capacity 2	4 x 1.5mm2
Earth Terminal Capacity 3	3 x 2.5mm2
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand
Earth Terminal Capacity 5	1 x 6mm2
Product Class 1	Face plate must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Additional Notes	Do NOT Connect to 230V Mains Voltage - Maximum 50 ballasts - To be used in conjunction with a 10 or 20A 2 Way Rocker Switch

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.com (WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 26/04/2024 E&OE