## **DATASHEET**



Code: IDPBC-W

# **GRID-IT | GRID-IT RANGE | Rocker Switch Modules**

### **Product Image**



### Wiring



### **Dimensions**

# Hemiton GRID-IT GDP 20AX Double Pole Rocker Module

| Insert Type                      | 20AX Double Pole Rocker Module   |
|----------------------------------|----------------------------------|
| Insert Colour                    | Bright Chrome/White              |
| EAN13 Barcode                    | 5051164039639                    |
| Commodity Code                   | 85363030                         |
| Luckins TSI                      | 387390983                        |
| ETIM Class                       | EC001590                         |
| Dimensions(Nominal)              | Module: Height = Width = Depth = |
| Weight                           | 31 GR                            |
| Switched Poles                   | Double                           |
| Current Rating                   | 20AX                             |
| Voltage                          | 220/250V AC                      |
| Maximum Load                     | 20 Amp inductive                 |
| Mains Frequency                  | 50Hz                             |
| IP Rating                        | IP2XD                            |
| Contact Gap Minimum              | 3mm                              |
| Terminal Capacity 1              | 5x1mm²                           |
| Terminal Capacity 2              | 4x1.5mm²                         |
| <b>Terminal Capacity 3</b>       | 2x2.5mm²                         |
| Terminal Capacity 4              | 1x4mm² Multi-strand              |
| Terminal Capacity 5              | 1x6mm²                           |
| Earth Terminal Capacity 1        | 6x1mm²                           |
| Earth Terminal Capacity 2        | 5x1.5mm²                         |
| Earth Terminal Capacity 3        | 3x2.5mm²                         |
| Earth Terminal Capacity 4        | 2x4mm² Multi-strand              |
| Earth Terminal Capacity 5        | 1x6mm²                           |
| Product Class 1                  | Face plate must be earthed       |
| Ambient Operating<br>Temperature | -5° to +40°C                     |
| Recommended Location             | Internal Use Only                |
| Maximum Installation<br>Altitude | 2000m                            |
| Standard/Approval                | BS EN 60669-1                    |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road Brislington Bristol BS4 5N7

**T:** +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.cor

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 19/05/2024 E&OE