## DATASHEET


Hamilton<sup>®</sup> making connections beautifully

## Code: IRRTPB-W GRID-IT | GRID-IT RANGE | Rocker Switch Modules

## Product Image




Wiring



Dimensions





In cost Trac	104X Duch To Make (Brook Datus ative Dealer Madula
Insert Type	10AX Push To Make/Break Retractive Rocker Module
Insert Colour	Polished Brass/White
EAN13 Barcode	5051164079734
Commodity Code	85363010
Luckins TSI	387391380
ETIM Class	EC001590
Dimensions(Nominal)	Module: Height = Width = Depth =
Weight	30 GR
Switched Poles	Single
Current Rating	10AX
Voltage	220/250V AC
Maximum Load	10 Amp inductive
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Terminal Capacity 1	5x1mm <sup>2</sup>
Terminal Capacity 2	4x1.5mm²
Terminal Capacity 3	1x2.5mm²
Terminal Capacity 4	1x4mm <sup>2</sup> Multi-strand
Terminal Capacity 5	1x6mm²
Earth Terminal Capacity 1	5x1mm <sup>2</sup>
Earth Terminal Capacity 2	4x1.5mm²
Earth Terminal Capacity 3	3x2.5mm²
Earth Terminal Capacity 4	1x4mm <sup>2</sup> Multi-strand
Earth Terminal Capacity 5	1x6mm²
Product Class 1	Face plate must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS EN 60669-1

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

**T:** +44 (0)1747 860088

**E:** info@hamilton-litestat.com | **W:** www.hamilton-litestat.com (WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 20/05/2024 E&OE