DATASHEET

Hamilton[®] making connections beautifully


Code: LD5258AB-ABB

Linea-Duo CFX | LINEA-DUO CFX RANGE | International Power Sockets


Product Image



Wiring



Dimensions



Insert Type	1 gang 15A 110V AC American Unswitched Socket
Insert Colour	Black
EAN13 Barcode	5017504036751
Commodity Code	85363010
Luckins TSI	398564012
ETIM Class	EC000125
Dimensions(Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	None
Current Rating	15 Amp
Voltage	110V AC
Maximum Load	15 Amp
Mains Frequency	60Hz
IP Rating	IP2XD
Contact Gap Minimum	None
Terminal Capacity 1	3x2.5mm²
Terminal Capacity 2	2x4mm²
Terminal Capacity 3	1x6mm ² Multi-strand
Product Class 1	Face plate must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS EN ISO 5733 + IEC 60884-1
Additional Notes	Shuttered :Yes
Patents And Trade Marks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.com (WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 16/04/2024 E&OE