DATASHEET




Code: LGXR22PB-SBW

Linea-Georgian CFX | LINEA-GEORGIAN CFX RANGE | Rocker Switches

Product Image



| Iľ | 1r | |
|----|----|--|
| | | |
| | | |
| | | |



Dimensions

| Insert Colour Polished Brass/White EAN13 Barcode 5017504813222 Commodity Code 85363010 Luckins TSI 391635689 ETIM Class EC001590 Dimensions(Nominal) Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 4x1.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Froduct Class 1 Must be earthed Ambient Operating 1 -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation Altitude | Local Torr | 2 10AY 2 W - Paul | |
|---|---------------------------|---|--|
| EAN13 Barcode 5017504813222 Commodity Code 85363010 Luckins TSI 391635689 ETIM Class EC001590 Dimensions(Nominal) Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 1x4mm² Multi-strand Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x4mm² Multi-strand Earth Terminal Capacity 7 1x4mm² Multi-strand Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 9 1x6mm² Earth Terminal Capacity 1 1x4mm² Multi-strand Earth Terminal Capacity 1 1x4mm² Multi-strand Earth Terminal Capacity 1 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating 1 -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Insert Type | 2 gang 10AX 2 Way Rocker | |
| Commodity Code Luckins TSI 391635689 ETIM Class EC001590 Dimensions(Nominal) Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x4mm² Multi-strand Earth Terminal Capacity 7 1x4mm² Multi-strand Earth Terminal Capacity 8 1x4mm² Multi-strand Earth Terminal Capacity 9 1x4mm² Multi-strand Earth Terminal Capacity 9 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m | | | |
| Luckins TSI 391635689 ETIM Class EC001590 Dimensions(Nominal) Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 1x4mm² Multi-strand Earth Terminal Capacity 3 1x2.5mm² Earth Terminal Capacity 3 1x41.5mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 3 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m | | 5017504813222 | |
| ETIM Class EC001590 Dimensions(Nominal) Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Forduct Class 1 Must be earthed Ambient Operating 15 to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Commodity Code | 85363010 | |
| Dimensions(Nominal) Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 1P Rating 1P2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Ix4mm² Multi-strand Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating 1 Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Luckins TSI | 391635689 | |
| Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 3 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Ix6mm² Earth Terminal Capacity 5 Fooduct Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation 2000m | ETIM Class | EC001590 | |
| Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP 2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 3 1x2.5mm² Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 Earth Terminal Capacity 3 1x4mm² Multi-strand Earth Terminal Capacity 3 1x4mm² Multi-strand Earth Terminal Capacity 3 Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Ix4mm² Multi-strand Earth Terminal Capacity 6 Earth Terminal Capacity 7 Ix6mm² Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Dimensions(Nominal) | | |
| Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 1x4mm² Multi-strand Earth Terminal Capacity 3 1x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | |
| Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 1x4mm² Multi-strand Earth Terminal Capacity 3 1x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Foduct Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Minimum Wall Box Depth | 25mm | |
| Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 1 1x6mm² Earth Terminal Capacity 2 1x4mm² Multi-strand Earth Terminal Capacity 3 1x2.5mm² Earth Terminal Capacity 3 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating 1-5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Switched Poles | Single | |
| Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Farth Terminal Capacity 5 1x6mm² Farth Terminal Capacity 6 1x4mm² Multi-strand Earth Terminal Capacity 7 1x6mm² Product Class 1 Must be earthed Ambient Operating 75° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Current Rating | 10AX | |
| Mains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15x1mm²Terminal Capacity 24x1.5mm²Terminal Capacity 31x2.5mm²Terminal Capacity 41x4mm² Multi-strandTerminal Capacity 51x6mm²Earth Terminal Capacity 15x1mm²Earth Terminal Capacity 24x1.5mm²Earth Terminal Capacity 33x2.5mm²Earth Terminal Capacity 41x4mm² Multi-strandEarth Terminal Capacity 51x6mm²Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation2000m | Voltage | 220/250V AC | |
| IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 3 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating 75° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Maximum Load | 10 Amp inductive | |
| Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Mains Frequency | 50Hz | |
| Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation 2000m | IP Rating | IP2XD | |
| Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating 75° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Contact Gap Minimum | 3mm | |
| Terminal Capacity 3 1x2.5mm² 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Terminal Capacity 1 | 5x1mm² | |
| Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Terminal Capacity 2 | 4x1.5mm² | |
| Terminal Capacity 5 | Terminal Capacity 3 | 1x2.5mm² | |
| Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Terminal Capacity 4 | 1x4mm² Multi-strand | |
| Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Terminal Capacity 5 | 1x6mm² | |
| Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Earth Terminal Capacity 1 | 5x1mm² | |
| Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Earth Terminal Capacity 2 | 4x1.5mm² | |
| Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Earth Terminal Capacity 3 | 3x2.5mm² | |
| Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Earth Terminal Capacity 4 | 1x4mm² Multi-strand | |
| Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Earth Terminal Capacity 5 | 1x6mm² | |
| Temperature Recommended Location Internal Use Only Maximum Installation 2000m | Product Class 1 | Must be earthed | |
| Maximum Installation 2000m | | -5° to +40°C | |
| | Recommended Location | Internal Use Only | |
| | | 2000m | |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.cor

(WFR


All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 06/05/2024 EXOF.

DATASHEET



Code: LGXR22PB-SBW

Linea-Georgian CFX | LINEA-GEORGIAN CFX RANGE | Rocker Switches



Standard/Approval BS EN 60669-1

Patents And Trade Marks

Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673