DATASHEET




Code: LGXR26PB-ABW

Linea-Georgian CFX | LINEA-GEORGIAN CFX RANGE | Rocker Switches

Product Image



Wiring



Dimensions

Insert Colour Polished Brass/White EAN13 Barcode 5017504823207 Commodity Code 85363010 Luckins TSI 391635919 ETIM Class EC001590 Dimensions(Nominal) Double: Height = 95.5mm Width = 154.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 1x4mm² Multi-strand Terminal Capacity 3 1x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 7 1x4mm² Multi-strand Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 9 1x6mm² Earth Terminal Capacity 1 1x4mm² Multi-strand Earth Terminal Capacity 1 1x6mm² Earth Terminal Capacity 1 1x6mm² Earth Terminal Capacity 3 1x2.5mm² Earth Terminal Capacity 3 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 7 1x6mm² Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 9 1x6mm² Ea	leased Torre	Coope 10AV 2 Wey Parkey
EAN13 Barcode 5017504823207 Commodity Code 85363010 Luckins TSI 391635919 ETIM Class EC001590 Dimensions(Nominal) Double: Height = 95.5mm Width = 154.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP 2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 1x4mm² Multi-strand Terminal Capacity 1 1x4mm² Multi-strand Earth Terminal Capacity 1 1x4mm² Multi-strand Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Insert Type	6 gang 10AX 2 Way Rocker
Commodity Code Luckins TSI 391635919 ETIM Class EC001590 Dimensions(Nominal) Double: Height = 95.5mm Width = 154.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x4mm² Multi-strand Earth Terminal Capacity 7 1x4mm² Multi-strand Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 9 1x6mm² Earth Ter		
Luckins TSI 391635919 ETIM Class EC001590 Dimensions(Nominal) Double: Height = 95.5mm Width = 154.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 1x4mm² Multi-strand Earth Terminal Capacity 3 1x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x4mm² Multi-strand Earth Terminal Capacity 7 1x4mm² Multi-strand Earth Terminal Capacity 8 1x4mm² Multi-strand Earth Terminal Capacity 9 1x6mm² Product Class 1 Must be earthed Ambient Operating 15° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m		
ETIM Class EC001590 Dimensions(Nominal) Double: Height = 95.5mm Width = 154.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 1x4mm² Multi-strand Earth Terminal Capacity 3 1x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation 2000m	-	85363010
Dimensions(Nominal) Double: Height = 95.5mm Width = 154.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency IP Rating IP2XD Contact Gap Minimum Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 3 Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Internal Capacity 6 Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Luckins TSI	391635919
Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 3 1x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation 2000m	ETIM Class	EC001590
Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP 2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 3 1x2.5mm² Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 3 1x4mm² Multi-strand Earth Terminal Capacity 3 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Internal Use Only Maximum Installation 2000m	Dimensions (Nominal)	·
Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 1x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x4mm² Multi-strand Earth Terminal Capacity 7 1x6mm² Product Class 1 Must be earthed Ambient Operating 1x6m² Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips
Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 1x2.5mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating 7-5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Minimum Wall Box Depth	25mm
Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 1 1x4mm² Multi-strand Earth Terminal Capacity 2 1x4mm² Multi-strand Earth Terminal Capacity 3 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating 1-5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Switched Poles	Single
Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Farth Terminal Capacity 5 1x6mm² Farth Terminal Capacity 6 1x4mm² Multi-strand Earth Terminal Capacity 7 1x6mm² Froduct Class 1 Must be earthed Ambient Operating 75° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Current Rating	10AX
Mains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15x1mm²Terminal Capacity 24x1.5mm²Terminal Capacity 31x2.5mm²Terminal Capacity 41x4mm² Multi-strandTerminal Capacity 51x6mm²Earth Terminal Capacity 15x1mm²Earth Terminal Capacity 24x1.5mm²Earth Terminal Capacity 33x2.5mm²Earth Terminal Capacity 41x4mm² Multi-strandEarth Terminal Capacity 51x6mm²Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation2000m	Voltage	220/250V AC
IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Farth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Maximum Load	10 Amp inductive
Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Mains Frequency	50Hz
Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation 2000m	IP Rating	IP2XD
Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating 75° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Contact Gap Minimum	3mm
Terminal Capacity 3 1x2.5mm² 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Terminal Capacity 1	5x1mm²
Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Terminal Capacity 2	4x1.5mm²
Terminal Capacity 5	Terminal Capacity 3	1x2.5mm²
Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Terminal Capacity 4	1x4mm² Multi-strand
Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Terminal Capacity 5	1x6mm²
Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Earth Terminal Capacity 1	5x1mm²
Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Earth Terminal Capacity 2	4x1.5mm²
Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Earth Terminal Capacity 3	3x2.5mm²
Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Earth Terminal Capacity 4	1x4mm² Multi-strand
Ambient Operating -5° to +40°C Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Earth Terminal Capacity 5	1x6mm²
Temperature Recommended Location Internal Use Only Maximum Installation 2000m	Product Class 1	Must be earthed
Maximum Installation 2000m		-5° to +40°C
	Recommended Location	Internal Use Only
		2000m

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road Brislington Bristol BS4 5N7

T: +44 (0)1747 860088

E: info@hamilton-litestat.com|**W:** www.hamilton-litestat.con

(WFR)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 28/04/2024 FXOF


DATASHEET



Design Certificate No. R21 = 2078674 SS2 = 2078673

Code: LGXR26PB-ABW

Linea-Georgian CFX | LINEA-GEORGIAN CFX RANGE | Rocker Switches



Standard/Approval BS EN 60669-1 **Patents And Trade Marks** Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered