



Code: LPXR24AB-ABB
Linea-Perlina CFX | LINEA-PERLINA CFX RANGE | Rocker Switches

Product Image



Wiring




Dimensions

| | |
|-------------------------------|---|
| Insert Type | 4 gang 10AX 2 Way Rocker |
| Insert Colour | Antique Brass/Black |
| EAN13 Barcode | 5017504862244 |
| Commodity Code | 85363010 |
| Luckins TSI | 391655274 |
| ETIM Class | EC001590 |
| Dimensions(Nominal) | Double: Height = 92.0mm Width = 151.0mm Depth = 4.0mm |
| Weight | 376 GR |
| Fixing Hole Centres | Box Fixing = 120.6mm Grid Fixing = CFX Clips |
| Minimum Wall Box Depth | 25mm |
| Switched Poles | Single |
| Current Rating | 10AX |
| Voltage | 220/250V AC |
| Maximum Load | 10 Amp inductive |
| Mains Frequency | 50Hz |
| IP Rating | IP2XD |
| Contact Gap Minimum | 3mm |
| Terminal Capacity 1 | 5x1mm ² |
| Terminal Capacity 2 | 4x1.5mm ² |
| Terminal Capacity 3 | 1x2.5mm ² |
| Terminal Capacity 4 | 1x4mm ² Multi-strand |
| Terminal Capacity 5 | 1x6mm ² |
| Earth Terminal Capacity 1 | 5x1mm ² |
| Earth Terminal Capacity 2 | 4x1.5mm ² |
| Earth Terminal Capacity 3 | 3x2.5mm ² |
| Earth Terminal Capacity 4 | 1x4mm ² Multi-strand |
| Earth Terminal Capacity 5 | 1x6mm ² |
| Product Class 1 | Must be earthed |
| Ambient Operating Temperature | -5° to +40°C |
| Recommended Location | Internal Use Only |

Code: LPXR24AB-ABB

Linea-Perlina CFX | LINEA-PERLINA CFX RANGE | Rocker Switches



| | |
|-------------------------------|--|
| Maximum Installation Altitude | 2000m |
| Standard/Approval | BS EN 60669-1 |
| Patents And Trade Marks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 |