DATASHEET




Code: LPXRRTAB-ABB

Linea-Perlina CFX | LINEA-PERLINA CFX RANGE | Rocker Switches

Product Image



Wiring



Dimensions

| Insert Type | 1 gang 10AX Push To Make/Push to Break Retractive Rocker |
|-------------------------------|---|
| Insert Colour | Antique Brass/Black |
| EAN13 Barcode | 5017504862190 |
| Commodity Code | 85363010 |
| Luckins TSI | 391653690 |
| ETIM Class | EC001590 |
| Dimensions(Nominal) | Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips |
| Minimum Wall Box Depth | 25mm |
| Switched Poles | Single |
| Current Rating | 10AX |
| Voltage | 220/250V AC |
| Maximum Load | 10 Amp inductive |
| Mains Frequency | 50Hz |
| IP Rating | IP2XD |
| Contact Gap Minimum | 3mm |
| Terminal Capacity 1 | 5x1mm² |
| Terminal Capacity 2 | 4x1.5mm² |
| Terminal Capacity 3 | 1x2.5mm² |
| Terminal Capacity 4 | 1x4mm² Multi-strand |
| Terminal Capacity 5 | 1x6mm² |
| Earth Terminal Capacity 1 | 5x1mm² |
| Earth Terminal Capacity 2 | 4x1.5mm² |
| Earth Terminal Capacity 3 | 3x2.5mm² |
| Earth Terminal Capacity 4 | 1x4mm² Multi-strand |
| Earth Terminal Capacity 5 | 1x6mm² |
| Product Class 1 | Must be earthed |
| Ambient Operating Temperature | -5° to +40°C |
| B | Internal Lie Only |

Internal Use Only

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.cor

Recommended Location

(WEB)


All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 04/05/2024 EXOF

DATASHEET



Code: LPXRRTAB-ABB

Linea-Perlina CFX | LINEA-PERLINA CFX RANGE | Rocker Switches



| Maximum Installation Altitude | 2000m |
|----------------------------------|---|
| Standard/Approval | BS EN 60669-1 |
| Patents And Trade Marks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 |