DATASHEET




Code: LPXRRTPB-PBB

Linea-Perlina CFX | LINEA-PERLINA CFX RANGE | Rocker Switches

Product Image



Wiring



Dimensions

Insert Type	1 gang 10AX Push To Make/Push to Break Retractive Rocker
Insert Colour	Polished Brass/Black
EAN13 Barcode	5017504872199
Commodity Code	85363010
Luckins TSI	391653755
ETIM Class	EC001590
Dimensions(Nominal)	Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	25mm
Switched Poles	Single
Current Rating	10AX
Voltage	220/250V AC
Maximum Load	10 Amp inductive
Mains Frequency	50Hz
IP Rating	IP2XD
IP Rating Contact Gap Minimum	IP2XD 3mm
_	=
Contact Gap Minimum	3mm
Contact Gap Minimum Terminal Capacity 1	3mm 5x1mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2	3mm 5x1mm² 4x1.5mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3	3mm 5x1mm² 4x1.5mm² 1x2.5mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4	3mm 5x1mm² 4x1.5mm² 1x2.5mm² 1x4mm² Multi-strand
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5	3mm 5x1mm² 4x1.5mm² 1x2.5mm² 1x4mm² Multi-strand 1x6mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1	3mm 5x1mm² 4x1.5mm² 1x2.5mm² 1x4mm² Multi-strand 1x6mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2	3mm 5x1mm² 4x1.5mm² 1x2.5mm² 1x4mm² Multi-strand 1x6mm² 5x1mm² 4x1.5mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3	3mm 5x1mm² 4x1.5mm² 1x2.5mm² 1x4mm² Multi-strand 1x6mm² 5x1mm² 4x1.5mm² 4x1.5mm²
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4	3mm 5x1mm² 4x1.5mm² 1x2.5mm² 1x4mm² Multi-strand 1x6mm² 5x1mm² 4x1.5mm² 4x1.5mm² 1x4mm² Multi-strand
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5	3mm 5x1mm² 4x1.5mm² 1x2.5mm² 1x4mm² Multi-strand 1x6mm² 5x1mm² 4x1.5mm² 4x1.5mm² 1x4mm² Multi-strand 1x6mm²

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

:: info(a)hamilton-litestat.com | **W**: www.hamilton-litestat.cor

(WFR


All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 03/05/2024 EXOE

DATASHEET



Code: LPXRRTPB-PBB

Linea-Perlina CFX | LINEA-PERLINA CFX RANGE | Rocker Switches



Maximum Installation Altitude	2000m
Standard/Approval	BS EN 60669-1
Patents And Trade Marks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588

T: +44 (0)1747 860088

: info@hamilton-litestat.com | W: www.hamilton-litestat.cor