# **DATASHEET**




Code: LPXSS2PB-ABW

## Linea-Perlina CFX | LINEA-PERLINA CFX RANGE | Power Sockets

#### **Product Image**



#### Wiring



#### Dimensions

| Insert Type                      | 2 gang 13A Double Pole Switched Socket                |
|----------------------------------|---|
| Insert Colour                    | Polished Brass/White                                  |
| EAN13 Barcode                    | 5017504893026   |
| <b>Commodity Code</b>            | 85363010  |
| Luckins TSI                      | 391657340   |
| ETIM Class                       | EC000125  |
| Dimensions(Nominal)              | Double: Height = 92.0mm Width = 151.0mm Depth = 4.0mm |
| Fixing Hole Centres              | Box Fixing = 120.6mm Grid Fixing = CFX Clips          |
| Minimum Wall Box Depth           | 35mm  |
| Switched Poles                   | Double  |
| Current Rating                   | 13 Amp  |
| Voltage                          | 220/250V AC   |
| Maximum Load                     | 13 Amp  |
| Mains Frequency                  | 50Hz  |
| IP Rating                        | IP2XD   |
| Contact Gap Minimum              | 3mm   |
| Terminal Capacity 1              | 4x2.5mm²  |
| Terminal Capacity 2              | 3x4mm²  |
| Terminal Capacity 3              | 2x6mm² Multi-Strand                                   |
| Terminal Capacity 4              | 1x10mm²   |
| Earth Terminal Capacity 1        | 4x2.5mm²  |
| Earth Terminal Capacity 2        | 3x4mm²  |
| Earth Terminal Capacity 3        | 2x6mm² Multi-Strand                                   |
| Earth Terminal Capacity 4        | 1x10mm²   |
| Product Class 1                  | Must be earthed                                       |
| Ambient Operating<br>Temperature | -5° to +40°C  |
| Recommended Location             | Internal Use Only                                     |
| Maximum Installation<br>Altitude | 2000m   |
| Standard/Approval                | BS 1363-2   |
| Additional Notes                 | Dual Earth: Yes                                       |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road Brislington Bristol BS4 5N7

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.cor

(WFR)


All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 06/05/2024 E&OE

## **DATASHEET**



Code: LPXSS2PB-ABW

## Linea-Perlina CFX | LINEA-PERLINA CFX RANGE | Power Sockets



#### **Patents And Trade Marks**

Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588

**T:** +44 (0)1747 860088

: info@hamilton-litestat.com | W: www.hamilton-litestat.cor