


Code: LPXT24AB-AB

Linea-Perlina CFX | LINEA-PERLINA CFX RANGE | Toggle Switches

Product Image



Wiring




Dimensions

Insert Type	4 gang 20AX 2 Way Toggle
Insert Colour	Antique Brass
EAN13 Barcode	5017504862282
Commodity Code	85363030
Luckins TSI	391656736
ETIM Class	EC001590
Dimensions(Nominal)	Double: Height = 92.0mm Width = 151.0mm Depth = 4.0mm
Weight	420 GR
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	Single
Current Rating	20AX
Voltage	220/250V AC
Maximum Load	20 Amp inductive
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Terminal Capacity 1	5x1mm ²
Terminal Capacity 2	4x1.5mm ²
Terminal Capacity 3	2x2.5mm ²
Terminal Capacity 4	2x4mm ² Multi-strand
Terminal Capacity 5	1x6mm ²
Earth Terminal Capacity 1	6x1mm ²
Earth Terminal Capacity 2	5x1.5mm ²
Earth Terminal Capacity 3	3x2.5mm ²
Earth Terminal Capacity 4	2x4mm ² Multi-strand
Earth Terminal Capacity 5	1x6mm ²
Product Class 1	Must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only

Code: LPXT24AB-AB

Linea-Perlina CFX | LINEA-PERLINA CFX RANGE | Toggle Switches



Maximum Installation Altitude	2000m
Standard/Approval	BS EN 60669-1
Patents And Trade Marks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588