
Hamilton<sup>®</sup> making connections beautifully

## Code: LPXT31PB-PB Linea-Perlina CFX | LINEA-PERLINA CFX RANGE | Toggle Switches

## Product Image



Wiring



Dimensions

In cost Time	1 con o 204 V Intermodiate Tagolo
Insert Type	1 gang 20AX Intermediate Toggle
Insert Colour	Polished Brass
EAN13 Barcode	5017504872298
Commodity Code	85363030
Luckins TSI	391656833
ETIM Class	EC001590
Dimensions(Nominal)	Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	Single
Current Rating	20AX
Voltage	220/250V AC
Maximum Load	20 Amp inductive
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Contact Gap Minimum Terminal Capacity 1	3mm 5x1mm <sup>2</sup>
-	
Terminal Capacity 1	5x1mm <sup>2</sup>
Terminal Capacity 1 Terminal Capacity 2	5x1mm <sup>2</sup> 4x1.5mm <sup>2</sup>
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3	5x1mm <sup>2</sup> 4x1.5mm <sup>2</sup> 2x2.5mm <sup>2</sup>
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4	5x1mm <sup>2</sup> 4x1.5mm <sup>2</sup> 2x2.5mm <sup>2</sup> 2x4mm <sup>2</sup> Multi-strand
Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5	5x1mm <sup>2</sup> 4x1.5mm <sup>2</sup> 2x2.5mm <sup>2</sup> 2x4mm <sup>2</sup> Multi-strand 1x6mm <sup>2</sup>
Terminal Capacity 1Terminal Capacity 2Terminal Capacity 3Terminal Capacity 4Terminal Capacity 5Earth Terminal Capacity 1	5x1mm <sup>2</sup> 4x1.5mm <sup>2</sup> 2x2.5mm <sup>2</sup> 2x4mm <sup>2</sup> Multi-strand 1x6mm <sup>2</sup> 6x1mm <sup>2</sup>
Terminal Capacity 1Terminal Capacity 2Terminal Capacity 3Terminal Capacity 4Terminal Capacity 5Earth Terminal Capacity 1Earth Terminal Capacity 2	5x1mm <sup>2</sup> 4x1.5mm <sup>2</sup> 2x2.5mm <sup>2</sup> 2x4mm <sup>2</sup> Multi-strand 1x6mm <sup>2</sup> 6x1mm <sup>2</sup>
Terminal Capacity 1Terminal Capacity 2Terminal Capacity 3Terminal Capacity 4Terminal Capacity 5Earth Terminal Capacity 1Earth Terminal Capacity 2Earth Terminal Capacity 3	5x1mm <sup>2</sup> 4x1.5mm <sup>2</sup> 2x2.5mm <sup>2</sup> 2x4mm <sup>2</sup> Multi-strand 1x6mm <sup>2</sup> 6x1mm <sup>2</sup> 5x1.5mm <sup>2</sup>
Terminal Capacity 1Terminal Capacity 2Terminal Capacity 3Terminal Capacity 4Terminal Capacity 5Earth Terminal Capacity 1Earth Terminal Capacity 2Earth Terminal Capacity 3Earth Terminal Capacity 3	5x1mm² 4x1.5mm² 2x2.5mm² 2x4mm² Multi-strand 1x6mm² 6x1mm² 5x1.5mm² 3x2.5mm² 2x4mm² Multi-strand
Terminal Capacity 1Terminal Capacity 2Terminal Capacity 3Terminal Capacity 4Terminal Capacity 5Earth Terminal Capacity 1Earth Terminal Capacity 2Earth Terminal Capacity 3Earth Terminal Capacity 3Earth Terminal Capacity 4Earth Terminal Capacity 5	5x1mm²   4x1.5mm²   2x2.5mm²   2x4mm² Multi-strand   1x6mm²   6x1mm²   5x1.5mm²   3x2.5mm²   2x4mm² Multi-strand   1x6mm²
Terminal Capacity 1Terminal Capacity 2Terminal Capacity 3Terminal Capacity 4Terminal Capacity 5Earth Terminal Capacity 1Earth Terminal Capacity 2Earth Terminal Capacity 3Earth Terminal Capacity 4Earth Terminal Capacity 5Earth Terminal Capacity 5Product Class 1Ambient Operating	5x1mm² 4x1.5mm² 2x2.5mm² 2x4mm² Multi-strand 1x6mm² 6x1mm² 5x1.5mm² 3x2.5mm² 2x4mm² Multi-strand 1x6mm² Multi-strand

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

**T:** +44 (0)1747 860088

E: info@hamilton-litestat.com W: www.hamilton-litestat.com (WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 01/05/2024 E&OE



making connections beautifully

## Code: LPXT31PB-PB

## Linea-Perlina CFX | LINEA-PERLINA CFX RANGE | Toggle Switches



R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

**T:** +44 (0)1747 860088

**E:** info@hamilton-litestat.com | **W:** www.hamilton-litestat.com (WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 01/05/2024 E&OE