DATASHEET




Code: LPXUS2AB-PBB

Linea-Perlina CFX | LINEA-PERLINA CFX RANGE | Power Sockets

Product Image



Wiring



Dimensions

Insert Type	1 gang 2A Unswitched Socket
Insert Colour	Black
EAN13 Barcode	5017504841041
Commodity Code	85363010
Luckins TSI	391658048
ETIM Class	EC000125
Dimensions(Nominal)	Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	None
Current Rating	2 Amp
Voltage	220/250V AC
Maximum Load	2 Amp
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	None
Terminal Capacity 1	5 x1mm²
Terminal Capacity 2	4x1.5mm²
Terminal Capacity 3	2x2.5mm²
Terminal Capacity 4	1x4mm²
Earth Terminal Capacity 1	5x1mm²
Earth Terminal Capacity 2	4 x 1.5mm2
Earth Terminal Capacity 3	2 x 2.5mm2
Earth Terminal Capacity 4	1 x 4mm2
Product Class 1	Must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS 546
Additional Notes	Shuttered: Yes


R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,

DATASHEET



Code: LPXUS2AB-PBB

Linea-Perlina CFX | LINEA-PERLINA CFX RANGE | Power Sockets



Patents And Trade Marks

Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588